

TRAILRIDER 2



LDV is a division of SAIC Motor, which is a Fortune Global 500 company and the 36th largest company in the world¹. SAIC Motor sold over 6 million vehicles in 2019 and has formed joint ventures with Volkswagen and General Motors. In 2009 SAIC Motor acquired the commercial vehicles division of British Motor Corporation which included LDV.



LDV T60 4WD DIESEL TRANSMISSION	Manual	AUTOMATIC
Engine		
Туре	Bosch high press	oo Diesel with sure common rail
 Maximum Power (kW)	direct fuel injection 120 @ 4000 rpm	
Maximum Torque (Nm)		')-2400 rpm
Displacement (cc)		96
Transmission		eed
Compression Ratio	15.9:1	15.9:1
No. of Valves	16	16
No. of Cylinders	4	4
Bore x Stroke (mm)	83x92	83x92
Ratios	6-speed Manual	6-speed Auto
 1st	4.657	4.065
2nd	2.594	2.371
	1.714	1.551
 4th	1.231	1.157
 5th	1	0.853
6th	0.806	0.674
Reverse	4.252	3.2
Final Drive	3.818	3.636
Low Range	2.48	2.48
Steering, Suspension and Brak	es	
Steering, Suspension and Brak Steering – Rack and Pinion Hydraulic Power Assisted	es	✓
Steering – Rack and Pinion		<i>y</i>
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double-	1	
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone	<i>y</i>	✓
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring	<i>J J</i>	<i>y</i>
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc	\frac{1}{\sqrt{1}}	<i>y y y</i>
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc	✓ ✓ ✓ ✓ Light Allo	\frac{1}{\sqrt{1}}
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions	✓ ✓ ✓ ✓ Light Allc	✓ ✓ ✓ ✓ oy 7.5Jx19
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions Tyre Dimensions	✓ ✓ ✓ ✓ Light Allc	✓ ✓ ✓ ✓ oy 7.5Jx19
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions Tyre Dimensions Spare Wheel and Tyre	✓ ✓ ✓ ✓ Light Allo 255/5 Steel 7Jx17	✓ ✓ ✓ ✓ oy 7.5Jx19
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions Tyre Dimensions Spare Wheel and Tyre Fuel and Emissions	✓ ✓ ✓ ✓ Light Allo 255/5 Steel 7Jx17	✓ ✓ ✓ ✓ Oy 7.5Jx19 55R19 245/65R17
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions Tyre Dimensions Spare Wheel and Tyre Fuel and Emissions Fuel Tank (Litres) Combined Fuel Consumption,	✓ ✓ ✓ ✓ Light Allc 255/5 Steel 7Jx17	✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions Tyre Dimensions Spare Wheel and Tyre Fuel and Emissions Fuel Tank (Litres) Combined Fuel Consumption, L/100km² Carbon Dioxide Emmissions	✓ ✓ ✓ ✓ Light Allo 255/5 Steel 7Jx17 7 8.5	✓ ✓ ✓ ✓ ✓ Øy 7.5Jx19 55R19 245/65R17
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions Tyre Dimensions Spare Wheel and Tyre Fuel and Emissions Fuel Tank (Litres) Combined Fuel Consumption, L/100km ² Carbon Dioxide Emmissions (g/km) ²	✓ ✓ ✓ ✓ Light Allo 255/5 Steel 7Jx17 7 8.5 223 Eur	
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions Tyre Dimensions Spare Wheel and Tyre Fuel and Emissions Fuel Tank (Litres) Combined Fuel Consumption, L/100km² Carbon Dioxide Emmissions (g/km)² Emissions Standard	✓ ✓ ✓ ✓ Light Allo 255/5 Steel 7Jx17 7 8.5 223 Eur	
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions Tyre Dimensions Spare Wheel and Tyre Fuel and Emissions Fuel Tank (Litres) Combined Fuel Consumption, L/100km² Carbon Dioxide Emmissions (g/km)² Emissions Standard Capacities, Dimensions and Weel	✓ ✓ ✓ ✓ ✓ Light Allo 255/5 Steel 7Jx17 7 8.5 223 Eur	
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions Tyre Dimensions Spare Wheel and Tyre Fuel and Emissions Fuel Tank (Litres) Combined Fuel Consumption, L/100km² Carbon Dioxide Emmissions (g/km)² Emissions Standard Capacities, Dimensions and Wand Approach Angle (unladen, degrees)	✓ ✓ ✓ ✓ Light Allo 255/5 Steel 7Jx17 7 8.5 223 Eur	
Steering – Rack and Pinion Hydraulic Power Assisted Front Suspension – Double- Wishbone Rear Suspension – Leaf-Spring Brakes – Front, disc Brakes – Rear, disc Wheel Dimensions Tyre Dimensions Spare Wheel and Tyre Fuel and Emissions Fuel Tank (Litres) Combined Fuel Consumption, L/100km² Carbon Dioxide Emmissions (g/km)² Emissions Standard Capacities, Dimensions and Weather Angle (unladen, degrees) Departure Angle (unladen, degrees) Front Overhang (mm) – Excluding	✓ ✓ ✓ ✓ Light Allo 255/5 Steel 7Jx17 7 8.5 223 Eur eights 27 24.2 942	

LDV T60 4WD DIESEL	TRAILRIDER 2	
TRANSMISSION	Manual	Automatic
Overall Length (mm) – Excluding Nudge Bar	5365	5365
Overall Height (mm)	1850	1850
Overall Width (Exterior Mirrors extended) (mm)	2145	2145
Overall Width (Exterior Mirrors folded) (mm)	1900	1900
Rear Overhang (mm)	1268	1268
Ramp Breakover Angle (degrees)	21.3°	21.3°
Turning Circle (kerb to kerb) (m)	12.6	12.6
Wading Depth (mm)	550	550
Wheelbase (mm)	3155	3155
Tub Box Width – Pick-Up Box (mm)	1510	1510
Tub Box Width of Rear Opening (mm)	1430	1430
Tub Height – at Centreline of Axle (mm)	530	530
Tub Height – Floor Height to Ground	820	820
Tub Length – at Floor (mm)	1525	1525
Tub Length – Top of Box mm)	1485	1485
Tub Width – Between Wheelarches (mm)	1131	1131
2nd Row Headroom (mm)	980	980
2nd Row Legroom (mm)	958	958
2nd Row Shoulder Room (mm)	1463	1463
Front Headroom (mm)	1010	1010
Front Legroom (mm)	1053	1053
Front Shoulder Room (mm)	1483	1483
Axle Load Capacity – Front (kg)	1280	1310
Axle Load Capacity – Rear (kg)	1620	1590
Gross Combined Vehicle Mass (kg)	5900	5900
Gross Vehicle Mass (kg)	2900	2900
Tare Weight (kg)	2005	2035
Payload (kg) ³	895	865
Towing Capacity – Braked (kg)	3000	3000
Towing Capacity – Unbraked (kg)	750	750

Safety, Security and Driver Assistance

5 Star ANCAP Safety Rating	✓	✓
2 Smart Keys	1	1
360° View Camera	1	1
Airbags (6) – Driver and front passenger airbags (2), side bags (2), curtain bags (2)	√	✓
Seat Belts Front Dual Pretensioning	✓	1
Child Anchoring – ISOFIX + Top Tether (2)	√	✓
Daytime Running Lights	✓	1
Adaptive Front-Lighting System (AFS)	√	✓
Blind Spot Monitor ⁴	1	1
Fatigue Reminder and Attention Assist ⁴	√	1

LDV T60 4WD DIESEL	TRAILRIDER 2	
TRANSMISSION	Manual	Automatic
Anti-Lock Braking System (ABS)		/
Electronic Brake Assist (EBA) Electronic Brake-force Distribution	<u> </u>	V
(EBD)	√	/
Electronic Stability Program (ESP)	✓	√
Hill Descent Control (HDC)	✓	√
Hill-Start Assist System (HAS)	✓	/
Roll Movement Intervention (RMI)	✓	✓
Traction Control System (TCS)	✓	/
Vehicle Dynamics Control (VDC)	✓	✓
Rear On Demand Differential Lock ⁵	✓	✓
Engine Immobiliser	✓	✓
Fog Lights	✓	✓
Keyless Entry and Start	✓	✓
Lockable Glove Box	✓	✓
Rear Parking Sensors	✓	✓
Reversing Camera	✓	/
Tyre Pressure Monitoring System (TPMS)	√	1
Lane Departure Warning ⁴	✓	/
Exterior		
Mountain Top Roll Cover – Lockable	√	/
Nudge Bar – Black	✓	/
Side Steps – Black	✓	✓
Sports Bar – Black	✓	/
Tub Liner – Spray-In	✓	✓
Side Mirrors – Heated and Auto Folding	✓	/
Tub Cargo Tie Down Hooks (4)	✓	✓
Mudflaps	✓	1
LED Headlights – Auto Dusk Sensing	✓	✓
Roof Rails	✓	✓
Rain Sensing Windscreen Wipers	✓	/
Comfort and Convenience		
Steering column – Height adjustable	√	✓
12V Power Outlet (1)	✓	/
Air Conditioning – Climate Control	✓	√
Cruise Control	✓	/
Rear View Mirror – Auto Dimming	✓	/
Leather Bound Multi-function	<u> </u>	/
Steering Wheel ⁶ Cup Holder (2)		
Cup Holder (2)	V	· ·
Seating		
5 Seats	✓	1
Front Row Seats – 6 way Electronic adjustment with Heating	✓	1
		+

Leather Trimmed Seats 6

TRAILRIDER 2	
Manual	Automatic

6 Speakers	1	1
10 Inch Touch Screen Entertainment System	1	1
AM/FM Stereo Radio, Bluetooth and MP5	1	1
Apple CarPlay® / Smartphone Connectivity	1	1
USB Ports (2)	1	1

Warranty and Roadside Assist 7

5 year/130,000km (whichever occurs first) Warranty	✓	✓
5 year/130,000km (whichever occurs first) Roadside Assist	✓	✓

Servicing

First Scheduled Service Free ⁹ (6 months or 5,000km, whichever comes first)	✓	1
--	---	---

Paint Colours Available



- Figures according to ADR 81/02 derived from laboratory testing. Factors
 including but not limited to driving style, road and traffic conditions,
 environmental influences, vehicle condition and accessories fitted, will
 in practice in the real world lead to figures which generally differ from
 those advertised. Advertised figures are meant for comparison amongst
 vehicles only.
- 3. Payload and tare weight figures are based on vehicle certification. It is the driver's responsibility to ensure: weight of fully loaded vehicles do not exceed GVM; front and rear axle load limits are not individually exceeded; the combined weight of the fully loaded vehicle (including tow ball download when towing) and trailer does not exceed the GCM; compliance to State and Territory towing regulations. Payload is the combined value of occupants, luggage, cargo, added options, accessories and tow ball download (when towing). Tare weight includes the vehicle with 10 litres of fuel and all standard equipment excluding occupants. Additional weights of optional features, occupants, luggage, cargo, accessories and tow ball download (when towing) must be taken into account when calculating payload and tare weight. When a genuine tow bar with wiring is fitted, and trailer is attached, parking sensors will be disabled.
- 4. Safety technologies may not operate optimally under all driving conditions, operation and effectiveness depends on many factors. Driver is responsible for safe and attentive driving. Safety technologies are not a substitute for the the driver's control over the vehicle. See owner's manual for complete details.
- 5. Self engages when required under 30 km/h.
- ${\small 6.\ Leather\ accented\ features\ and\ upholstery\ contain\ some\ synthetic\ materials.}$
- 7. Subject to terms, conditions and exclusions at Idvautomotive.com.au
- 9. It is the owner's responsibility to present the vehicle at an authorised LDV dealership for the service within +/- 60 days or 1,500kms of the first scheduled service interval (being 5,000kms or 6 months from the date of first registration (whichever comes first)). The scheduled service excludes fair wear and tear items and any additional work or components required that are not set out in the service schedule located in the owners service and warranty booklet. Not transferrable or redeemable for cash.

All information in this document is correct at time of publication however variations may occur from time to time and Ateco Automotive Pty Ltd insofar as is permitted by law to do so, shall not be liable in any way as a result of any reliance by any person on anything contained in this document.





