The LDV T60 UTE



LDV is a division of SAIC Motor, which is a Fortune Global 500 company and the 36th largest company in the world¹. SAIC Motor sold over 6 million vehicles in 2019 and has formed joint ventures with Volkswagen and General Motors. In 2009 SAIC Motor acquired the commercial vehicles division of British Motor Corporation which included LDV.



LDV T60 UTE 4WD DIESEL	T60	Pro	T60	T60 Luxe		ega Tub	LDV T60 UTE 4WD DIESEL	T60 Pro		T60 Luxe		T60 Mega Tub	
TRANSMISSION	Manual	Auto	Manual	Auto	Manual	Auto	TRANSMISSION	Manual	Auto	Manual	Auto	Manual	Auto
Engine	'	'	'		'	!	Overall Length (mm)	5365	5365	5365	5365	5680	5680
Туре			Diesel wit				Overall Height (Including Roof Rails) (mm)	1840	1840	1840	1840	1850	1850
Maximum Power (kW)	Turbocharger (VGT) and Intercooler 110 @ 3400 rpm			Overall Width (Exterior Mirrors extended) (mm)	2145	2145	2145	2145	2145	2145			
Maximum Torque (Nm)	360 @ 1600-2800 rpm			Overall Width (Exterior									
Displacement (cc)	2776				Mirrors folded) (mm)	1900	1900	1900	1900	1900	1900		
Transmission			6 Sp	eed			Rear Overhang (mm)	1268	1268	1268	1268	1268	1268
Compression Ratio	17:1	17:1	17:1	17:1	17:1	17:1	Ramp Breakover Angle (degrees)	21.3°	21.3°	21.3°	21.3°	21.3°	21.3°
No. of Valves	16	16	16	16	16	16	Turning Circle (kerb to	40.5	10.6	40.5	40.6	40.0	40.0
No. of Cylinders	4	4	4	4	4	4	kerb) (m)	12.6	12.6	12.6	12.6	13.8	13.8
Bore x Stroke (mm)	94x100	94x100	94x100	94x100	94x100	94x100	Wading Depth (mm)	550	550	550	550	550	550
Manual Shift Mode for Auto Models	_	1	-	✓	-	1	Wheelbase (mm)	3155	3155	3155	3155	3470	3470
Eco/Power Mode	-	1	-	√	-	1	Tub Box Width – Pick-Up Box (mm) without tub liner	1510	1510	1510	1510	1510	1510
Ratios	6-speed Manual	6-speed Auto	6-speed Manual	6-speed Auto	6-speed Manual	6-speed Auto	Tub Box Width of Rear Opening (mm) without tub liner	1430	1430	1430	1430	1430	1430
1st	4.371	4.065	4.371	4.065	4.371	4.065	Tub Height – at Centreline						
2nd	2.27	2.371	2.27	2.371	2.27	2.371	of Axle (mm) without tub liner	530	530	530	530	530	530
3rd	1.443	1.551	1.443	1.551	1.443	1.551	Tub Length – at Floor	1485	1485	1485	1485	1760	1760
4th	1	1.157	1	1.157	1	1.157	(mm) without tub liner Tub Length – Top of Box						
5th 6th	0.817	0.853	0.817	0.853	0.817	0.853	(mm) without tub liner	1525	1525	1525	1525	1800	1800
Reverse	0.679 4.253	0.674 3.2	0.679 4.253	0.674 3.2	0.679 4.253	3.2	Tub Width – Between Wheelarches (mm) without tub liner	1131	1131	1131	1131	1131	1131
Final Drive	3.818	3.636	3.818	3.636	3.818	3.636							
Low Range	2.48	2.48	2.48	2.48	2.48	2.48	2nd Row Headroom (mm)	980	980	980	980	980	980
Steering Syspensian	and Dun	lean				<u> </u>	2nd Row Legroom (mm)	958	958	958	958	958	958
Steering, Suspension a		kes					2nd Row Shoulder Room (mm)	1463	1463	1463	1463	1463	1463
Steering – Rack and Pinion Hydraulic Power Assisted	✓	1	✓	✓	✓	1	Front Headroom (mm)	1010	1010	1010	1010	1010	1010
Front Suspension – Double-Wishbone	1	1	1	1	1	1	Front Legroom (mm) Front Shoulder Room	1053	1053	1053	1053	1053	1053
Rear Suspension – Heavy Duty Leaf-Spring	1	1	_	_	_	-	(mm)	1483	1483	1483	1483	1483	1483
Rear Suspension – Leaf-Spring	-	-	/	1	1	1	Axle Load Capacity – Front (kg)	1220	1220	1190	1220	1300	1290
Brakes – Front, disc	1	1	√	✓	1	1	Axle Load Capacity – Rear (kg)	1830	1830	1760	1730	1600	1610
Brakes – Rear, disc Wheels and Tyres	1	1	1	✓	19"	√ x 7.5J	Gross Combined Vehicle	6050	6050	5950	5950	5950	5950
wheels and Tyres	17" x 7J Alloy Wheels with Alloy Wheels with 245/65 R17 Tyres R19 Tyres					Wheels	Mass (kg) Gross Vehicle Mass (kg)	3050	3050	2950	2950	2900	2900
							Tare Weight (kg) ³	1895	1925	1945	2005	1970	2030
Spare Wheel	17" x 7.5J 17" x 7.J Alloy Wheel with Alloy Temporary 245/65 R17 Tyre Spare 245/65 R17 Tyres						Payload (kg) ³	1025	995	875	815	880	868
						245/65	Towing Capacity – Braked (kg)	3000	3000	3000	3000	3000	3000
Fuel and Emissions					1 117		Towing Capacity – Unbraked (kg)	750	750	750	750	750	750
Fuel Tank (Litres)			7	5			. 0,		• .				
Combined Fuel Consumption, L/100km ²	8.8	9.6	8.8	9.6	8.8	9.6	Safety, Security and D 5 Star ANCAP Safety	river As	sistand	: e	/	/	
Carbon Dioxide Emmissions (g/km)	233	254	233	254	233	254	Rating 1 Remote Key and	<i>'</i>	/	_		_	
Emissions Standard			Eur	o 5			1 Normal Key						
Capacities, Dimension	s and W	/eights					2 Smart Keys Airbags (6) – Driver and	-	_	√	1	√	✓
Approach Angle (unladen, degrees)	27	27	27	27	27	27	front passenger airbags (2), side bags (2), full	1	1	1	✓	1	✓
Departure Angle (unladen, degrees)	24.2	24.2	24.2	24.2	24.2	24.2	length curtain bags (2) Seat Belts Front Dual	/	/	/	/	1	
Front Overhang (mm)	942	942	942	942	942	942	Pretensioning Child Anchoring ISOFIX I		•	_	•	•	•
Front Track/Rear Track (mm)		ı	1580/	1580	1	1	Child Anchoring – ISOFIX + Top Tether (2)	1	1	1	1	1	√
Ground Clearance	215	215	215	215	215	215	Daytime Running Lights – LED	1	1	1	1	1	✓

LDV T60 UTE 4WD DIESEL	T60	Pro	T60	Luxe	T60 Mega Tub		
TRANSMISSION	Manual	Auto	Manual	Auto	Manual	Auto	
Adaptive Front-Lighting System (AFS)	1	1	1	1	1	1	
Blind Spot Monitor ⁴	1	1	1	1	1	1	
Fatigue Reminder and Attention Assist ⁴	1	1	1	1	1	1	
Anti-Lock Braking System (ABS)	√	1	1	1	1	1	
Electronic Brake Assist (EBA)	✓	1	1	1	1	1	
Electronic Brake-force Distribution (EBD)	✓	1	1	1	1	1	
Electronic Stability Program (ESP)	✓	1	1	1	1	1	
Hill Descent Control (HDC)	✓	1	1	1	1	1	
Hill-Start Assist System (HAS)	1	1	1	1	1	1	
Roll Movement Intervention (RMI)	1	1	1	1	1	1	
Traction Control System (TCS)	✓	1	1	1	/	1	
Vehicle Dynamics Control (VDC)	1	1	1	1	/	1	
Rear On Demand Differential Lock ⁵	_	_	1	1	1	1	
Engine Immobiliser	1	1	1	1	1	1	
Fog Lights	✓	1	1	1	1	1	
Keyless Entry and Start	-	-	1	1	1	✓	
Remote Control Locking	✓	1	-	-	-	-	
Lockable Glove Box	✓	1	/	1	1	1	
Rear Parking Sensors	✓	1	1	1	1	1	
Reversing Camera	✓	1	1	1	1	✓	
Tyre Pressure Monitoring System (TPMS)	✓	1	1	1	1	1	
Lane Departure Warning ⁴	-	_	✓	✓	/	✓	
Exterior							
Side Mirrors – Heated and Auto Folding	ı	-	1	1	1	√	
Side Mirrors – Heated	✓	1	-	-	-	_	
Door handle – Body Colour	1	1	_		_	-	
Door handle – Chrome	-	-	1	1	1	1	
Tub Cargo Tie Down Hooks (4)	✓	1	1	1	1	✓	
Door Mirrors – Body colour	✓	1	-	-	_	-	
Door Mirrors – Chrome	-	-	1	1	1	✓	
Mudflaps – Front and Rear	✓	1	1	1	1	1	
LED Headlights – Auto Dusk Sensing	1	1	1	1	1	1	
Roof Rails	✓	1	1	1	1	1	
Rain Sensing Windscreen Wipers	✓	1	/	1	1	1	
Side Steps	√	1	1	1	1	✓	
Headboard	✓	1	-	-	-	_	
Sports Bar	-	_	1	1	1	1	
Tub Liner – Polythene Insert	✓	1	/	1	1	1	
Comfort and Convenie	nce			1			
Steering column – Height adjustable	✓	1	1	1	1	✓	
12V Power Outlet (1)	1	1	1	1	1	1	

LDV T60 UTE 4WD DIESEL	T60	Pro	T60	Luxe	T60 Mega Tub		
TRANSMISSION	Manual	Auto	Manual	Auto	Manual	Auto	
Air Conditioning	1	1	-	-	-	-	
Air Conditioning – Climate Control	-	/		1	1	1	
Cruise Control	1	1	1	/	1	1	
Rear View Mirror – Auto Dimming	-	/		1	1	1	
Rear View Mirror – Manual Dimming	1	1	-	-	-	_	
Multifunction Steering Wheel	<i>J J</i> – –		-				
Leather Bound Multi- function Steering Wheel ⁶	-	/ /		1	1	1	
Sunglass Holder	1	<i>J J J</i>		1	1	✓	
Cup Holder (2)	1	1	1	1	1	1	
Seating							
5 Seats	/	1	/	1	1	/	
Drivers Seat – 6 way Manual adjustment	1	1	-	-	_	_	
Passengers Seat – 4 way Manual adjustment	1	1	-	-	-	-	
Front Row Seats – 6 way Electronic adjustment with Heating	-	-	1	1	1	1	
Cloth Seats	1	1	-	-	-	_	
Leather Trimmed Seats ⁶	-	_	1	1	1	1	
Audio and Communica	ation						
6 Speakers	1	/	/	/	/	/	
10 Inch Touch Screen Entertainment System	1	1	1	1	1	✓	
AM/FM Stereo Radio, Bluetooth and MP5	1	1	1	1	1	✓	
Apple CarPlay® / Smartphone Connectivity	1	1	/ / /		1	1	
USB Ports (2)	1	1	/	/	/	1	
Warranty ⁷							
5 year/130,000km (whichever occurs first) Warranty	1	1	/	1	/	√	
5 year/130,000km (whichever occurs first) Roadside Assist	1	1	/ /		1	1	

- 2. Fuel consumption figures according to ADR 81/02 derived from laboratory testing. Factors including but not limited to driving style, road and traffic conditions, environmental influences, vehicle condition and accessories fitted, will in practice in the real world lead to figures which generally differ from those advertised. Advertised figures are meant for comparison amongst vehicles only.
- advertised. Advertised figures are meant for comparison amongst vehicles only.

 3. Payload and tare weight figures are based on vehicle certification. It is the driver's responsibility to ensure: weight of fully loaded vehicles do not exceed GVM; front and rear axle load limits are not individually exceeded; the combined weight of the fully loaded vehicle (including tow ball download when towing) and trailer does not exceed the GCM; compliance to State and Territory towing regulations. Payload is the combined value of occupants, luggage, cargo, added options, accessories and tow ball download (when towing). Tare weight includes the vehicle with 10 litres of fuel and all standard equipment excluding occupants. Additional weights of optional features, occupants, luggage, cargo, accessories and tow ball download (when towing) must be taken into account when calculating payload and tare weight. When a genuine tow bar with wiring is fitted, and trailer is attached, parking sensors will be disabled.

 4. Safety technologies may not operate optimally under all driving conditions
- 4. Safety technologies may not operate optimally under all driving conditions, operation and effectiveness depends on many factors. Driver is responsible for safe and attentive driving. Safety technologies are not a subsitute for the the driver's control over the vehicle. See owner's manual for complete details.
- 5. Self engages when required under 30 km/h.
- 6. Leather accented features and upholstery contain some synthetic materials.
- 7. Subject to terms, conditions and exclusions at Idvautomotive.com.au

All information in this document is correct at time of publication however variations may occur from time to time and Ateco Automotive Pty Ltd insofar as is permitted by law to do so, shall not be liable in any way as a result of any reliance by any person on anything contained in this document.





