

THUNDER*RIPPER*[™]

Creating Wealth Through Healthy Soils



THE COST-EFFECTIVE DEEP RIPPING SOLUTION TO MAXIMISE YOUR YIELD POTENTIAL!



Sustaining Farms to Sustain the World

1800 194 131
www.k-line.net.au
sales@k-line.net.au



THUNDER RIPPER™

The K-Line Ag ThunderRipper™ is a heavy duty yet compact Ripper, built to shatter compacted soils and improve root penetration. It is fitted with tynes that reach deep into hard pans to break up and lift soils, allowing room for plant development, nutrient and moisture entry, and accumulation of organic materials.

ThunderRipper™ Features

- Optional tyne spacings available to suit your operation and soil type
- Heavy duty deep-ripping tynes with shear pin system can rip to a depth of approx. 450-500mm
- Heavy duty adjustable knifing roller for soil conditioning and clod busting
- Extremely robust construction with heavy duty main frame members (150 x 150 x 9mm)
- Optional Depth Gauge Wheels
- 680mm Underframe Clearance

ThunderRipper™ Specifications

MODEL	DESCRIPTION	OPERATING WIDTH	TRANSPORT WIDTH	HP	ROLLER	NO. OF TYNES	TYNE SPACING RANGE	WHEEL EQUIPMENT
3400D	3PL	2.5m-6m	2.5m-6m	100-400	standard	5-13	325mm & 500-550mm*	
3445R	Trailing non-fold	4.5m	4.5m	250-400	standard	9-13	410mm & 500mm	425/65 RR22-5
346OR	Trailing non-fold	6m	6m	300-550	standard	11-13	462mm & 550mm	425/65 RR22-5
3445P	Trailing, folding	4.5m	2.5m	250-400	standard	9-11	410mm & 500mm	425/65 RR22-5
346OP	Trailing, folding	6m	2.5m	300-550	standard	13	462mm	425/65 RR22-5

*3400D spacing is machine size dependent, contact K-Line Ag for specific machine spacing. These specifications are subject to change without prior notice.

Ripper Leg



Heavy duty shear-pin cast leg with Tungsten point and replaceable shinguards mounted to 150x150x9mm SHS



3445P Hydraulic-fold Trailing Unit designed for the contractor. Narrow transport width (2.5m), available in 4.5m and 6m models.



346OR Rigid-Frame Trailing Unit available in 4.5m and 6m Models.