

# IRADENIT AXLE BACK



ADAPTABLE. MANOEUVRABLE. BUILT FOR BUSINESS.

## The Mack Trident range compliments our existing line-haul application range.

The Trident with axle back configuration provides the best possible turning circle and weight distribution over the steer axle.

Coupled with 131 tonnes of gross combination mass (GCM), the Mack Trident Axle Back will handle long haul, B-double or logging assignments with ease.

#### **FEATURES**

- » Perfect for long haul, B-double or logging applications
- » Powered by the Mack MP8 535Hp or 500Hp engine delivering up to 1920 lb-ft of torque
- » The front axle position offers excellent manoeuvrability
- » *m*DRIVE automated manual transmission takes all the effort out of gear changes
- » Quiet and comfortable cab
- » Great fuel economy and low emissions
- » Optional Road Stability Advantage rollover prevention
- » Mack Grade Gripper hill start assist

Designed and built in Australia for Australian conditions



#### TRIDENT 6X4 AB DAY CAB WITH B-DOUBLE LOG JINKERS



TRIDENT 6X4 AB 36" HIGH-RISE SLEEPER WITH 26METRE B-DOUBLE



\*Model shown is for illustration purposes only. Contact your Authorised Dealer for details of current options available.

### **BORN READY.**

## TRIDENT AXLE BACK

## **ENGINE & TRANSMISSION**

ENGINE			FAN				
<ul> <li>» MACK MP8 12.8 litre</li> <li>» MAXI-CRUISE torque settings</li> <li>» Selective Catalytic Reduction (SCR)</li> <li>» Emission Level Euro5 (ADR80/03)</li> </ul>			<ul> <li>» Behr Visco drive (electric over viscous fan clutch)</li> <li>» 750mm (29.5") 9-blade nylon fan</li> </ul>				
			RADIATOR				
		535	» NL3, Frontal area 1,435in <sup>2</sup>				
Torque (lb-ft)	1840	1920	EXHAUST				
ENGINE BRAKE			» Single RHS frame mounted catalyst with stainless heat shield				
» Advanced PowerLeash engine brake » Engine retarding power up to 315Kw (495hp) @ 2,100rpm			<ul> <li>Outlet single RHS 152mm (6") vertical exhaust (Day Cab)</li> <li>Outlet twin 152mm (6") vertical exhaust (Day Cab/Sleeper Cab Outlet single 127mm (5") underframe outlet (optional)</li> <li>Exhaust tip height above ground 3.5mtr</li> <li>Exhaust tip height above ground 4.2mtr (optional)</li> </ul>				
AIR INTAKE & FILTER							
» Donaldson 279mm (11") single dry type element, mounted under bonnet			TRANSMISSION				
<ul> <li>Painted under bornnet</li> <li>Painted steel dust extractors and external raised air intakes mounted in front of the cabin 'A' pillars</li> </ul>			» Manual and Automated Manual transmissions (Refer Transmission Chart)				
FILTERS			» Transmission oil cooler				
» 2 full flow and 1 by	pass eng	jine mounted oil filters	CLUTCH				
» 2 step dual engine mounted fuel filters/water separator			<ul> <li>» Eaton 394mm (15.5") Easy Pedal with VCT Plus</li> <li>» Eaton 'Solo' with VCT Plus (optional)</li> <li>» SACHS 430mm (17") Single Plate (mDRIVE only)</li> </ul>				
AIR COMPRESSOR							
» 2 CYL. 900 litres/n	nin WAB	CO compressor	» Air assist clutch release				
AIR DRYER			DRIVELINE				
» Bendix AD-IS air dryer			» Spicer 10 series				
ALTERNATOR			» SPL Maintenance Free (option)				
» Leece Neville 12volt/160Amp Brushed			PTO OPTIONS				
» Leece Neville 12volt/160Amp Brushless (optional)			» Rear of engine PTO (CA)				
» Leece Neville 12volt/185Amp Brushless (optional)			» Transmission mounted PTO (optional on mDRIVE) Draw bit switch witting and activutes (aDDI)(C) (actional)				
STARTER			» Prep kit, switch, wiring and software ( <i>m</i> DRIVE) (optional)				

#### TRANSMISSION SPECIFICATIONS

» Key type start and stop

MODEL	MAX TORQUE CAPACITY	FWD GEARS	REV GEARS	LO/HI	ТҮРЕ
AT2612D (Direct)	1,920ft–lbs	12	2	14.94/1.0	Fully Automated Manual
RTLO20918	2,050ft-lbs	18	4	14.40/0.73	Manual
RTLO22918	2,250ft-lbs	18	4	14.40/0.73	Manual
	AT2612D (Direct) RTLO20918	MODELCAPACITYAT2612D (Direct)1,920ft-lbsRTLO209182,050ft-lbs	MODELCAPACITYFWD GEARSAT2612D (Direct)1,920ft-lbs12RTLO209182,050ft-lbs18	AT2612D (Direct)         1,920ft–lbs         12         2           RTLO20918         2,050ft–lbs         18         4	AT2612D (Direct)         1,920ft-lbs         12         2         14.94/1.0           RTLO20918         2,050ft-lbs         18         4         14.40/0.73

## **AXLES, SUSPENSIONS & BRAKES**

FRONT AXLE	REAR SUSPENSION				
<ul> <li>Mack FXL with unitised hubs (Refer Steer Axle Chart)</li> <li>Axle position: Axle back: 1,297mm Bumper to Front Axle</li> </ul>	» Air and mechanical spring options (Refer Drive Axle Chart) » Ratings 18 to 21 tonne				
FRONT SUSPENSION	<ul> <li>» Out board mounted shock absorbers</li> <li>» In-board mounted shock absorbers (optional on AL460 only)</li> </ul>				
» 1,321mm (52") long springs (Refer Steer Axle Chart)	NB: "Road Friendly" capable suspensions available - speak with your Authorised Deale				
BRAKES	regarding options.				
» Front and Rear automatic slack adjusters	INTER-AXLE/WHEEL LOCKS				
» Type 20 Front brake boosters	» DCDL one axle only (vendor axles only)				
» S' Cam with iron drums	» DCDL's on both axles (optional) » Mack Power Divider (standard with Mack axles)				
» S' Cam with centrifuse drums (optional)					
» Type 30/30 Rear brake boosters	WHEELS				
» Low tare alloy hubs (optional)	» 10-stud 8¼" (285mm PCD) steel disc				
» ABS or (optional) ABS with Traction Control	» 10-stud options:				
» Grade Gripper - hill start assist	10-stud 8¼" (285mm PCD) machine buff / polished alloy /				
» Road Stability Advantage (ESP - Electronic Stability Program)	DURABRIGHT alloy discs 10-stud 9" (285mm PCD) polished alloy or DURABRIGHT alloy discs TYRES				
- Optional					
STEERING GEAR					
» Sheppard M100P	» Bridgestone / Michelin tyres				
» Steering ratio 18.9:1					
REAR AXLES					
<ul> <li>Mack, Meritor and Dana axle options (Refer Drive Axle Chart)</li> <li>Ratings 20 to 22.7 tonne</li> </ul>					

## STEER AXLE SPECIFICATIONS

MAKE	MODEL	CAPACITY	SUSPENSION*	COMMENTS
Mack	FXL 14.6	14,600lbs (6.6t)	(P3,M7)	Standard axle
Mack (Aus)	Twin FXL 14.6	29,200lbs (13t)	(P3)	Load share (CA)
Mack (NZ)	Twin FXL 14.6	29,200lbs (13t)	(P3)	Non-load share (CA)
Meritor	FG941	14,600lbs (6.6t)	(P3,M7)	Disc brakes (CA)

#### **DRIVE AXLE SPECIFICATIONS**

MAKE	MODEL	CAPACITY	RATIOS**	RATIOS (mDRIVE)	SUSPENSION
Mack	S440 (150/200 series)	44,000lbs (20t)	4.19, 4.50, 4.80 / 4.35, 4.73, 5.02	3.11, 3.25, 3.40	AL460
Mack	S462 (150/200 series)	46,000lbs (21t)	4.19, 4.50, 4.80 / 4.35, 4.73, 5.02	3.11, 3.25, 3.40	AD246
Meritor	RT46-160	46,000lbs (21t)	4.30, 4.56, 4.89	3.07, 3.21, 3.42	AL460 / AP460 / AD246 / MIL-H
Dana	D46-170	46,000lbs (21t)	4.30, 4.56, 4.78	3.07, 3.21, 3.42	AL460 (CA only)
Dana	D50-170	50,000lbs (22.7t)	4.30, 4.56, 4.78	3.07, 3.21, 3.42	AD246 (CA only)

\*\* Mack ratios in GOLD relate to Mack 150 series carriers/Mack ratios in BLACK relate to Mack 200 series carriers

## CHASSIS

CHASSIS	ADBLUE TANKS				
» Advantage 300mm x 90mm x 8mm <sup>†</sup> 156,000psi/RBM 1,940,000in Ib	» AdBlue Tank, kerbside (LHS) location 125 litre stainless steel 26" round				
<ul> <li>» Advantage 300mm x 90mm x 9.5mm<sup>†</sup></li> <li>184,000psi/RBM 2,240,000in Ib</li> <li><sup>†</sup> Dependent on wheel base and axle capacity</li> </ul>	150 litre stainless steel 26" round (optional) 150 litre stainless steel D-shaped (optional) 200 litre stainless steel D-shaped (optional)				
WHEELBASE	REMOTE BREATHERS				
» 4485mm (176.6") to 5795mm (242")	» Transmission, fuel and axle remote breather kit (optional)     CHASSIS ACCESS STEP     » Staired and perforated 2 step design (optional)				
AFTERFRAME (REAR OVERHANG)					
» 1365mm (53.7") to 2,810mm (110.6")					
» All chassis lengths can be specified with tapered rail ends	BATTERIES				
CAB SUPPORT    » Front: Two metalistic pivot mounts  » Rear: Air isolation with dual cabin shock absorbers  » Fully suspended cab  » Rear panard rod	<ul> <li>» 12volt Bulldog batteries, high capacity (620 CCA)</li> <li>» LH and RH frame mounted with black battery box cover</li> <li>» Polished aluminium battery box cover (optional)</li> <li>» Batteries mounted in sleeper if fitted</li> <li>» Stacked battery box (CA only)</li> </ul>				
BULLBAR/ BUMPER/ FUPS	TRAILER CONNECTIONS				
<ul> <li>» Light weight alloy bumper</li> <li>» Polished alloy bullbar (optional)</li> <li>» Front Underrun Protection</li> </ul>	<ul> <li>» Trailer - connections back of cab</li> <li>» Trailer - connections back of cab and rear of frame (optional)</li> <li>» Rigid - trailer connections rear of frame</li> <li>» Air: Service and emergency with blanking plugs</li> </ul>				
FUEL TANKS	» Electrical: 12volt 7-pin female base with HD 5mm <sup>2</sup> cabling				
<ul> <li>» Stainless Steel D tank straps (CA)</li> <li>» 26" round polished alloy tanks (Refer Wheelbase Chart)</li> </ul>	ELECTRICAL				
» Large capacity polished D-shaped tanks (optional)	<ul> <li>» Chassis harness with protective conduit</li> <li>» Electrical prep kit, Body Builder chassis connections (optional)</li> </ul>				

#### TRIDENT AB WHEELBASE SPECIFICATIONS

WHEELBASE (mm)	EXHAUST TO CENTRE OF DRIVE (mm)					MAXIMUM FUEL CAPACITY	ADBLUE TANK CAPACITY	TURNING CIRCLE (m)	
	Day Cab	Super Cab	36" B/D Sleeper	40" Sleeper	46" Sleeper	52" Sleeper			Kerb to Kerb
Bumper to Back of Cab	2960	3570	3670	3775	3930	4080			
4510	2727	2237					700L	125L	16.1
4710	2927	2437	2137	2232			1000L	125L	16.7
4860	3077	2587	2487	2382	2227		1400L	200L	17.2
5060	3277	2437		2582	2427	2277	1400L	200L	17.8
5210	3427				2577	2427	1400L	200L	18.3
5360	3577					2577	1700L	150L	18.7

\* Other sleeper sizes available, speak with your Authorised Dealer for options

## CAB

#### TELEMATICS

Mack telematics system - speak with your Authorised Dealer for further information.

#### SHELL

» Fusion Cab, ECE29 (cab strength test) compliant

» Two piece windscreen

#### **SLEEPER OPTIONS**

» 710mm (28") Super Cab with rear cabin extension

» 911mm (36") High-rise premium sleeper - 3 door (CA)

» 1,015mm (40") Mid-rise premium sleeper – 4 door

» 1,170mm (46") Mid-rise premium sleeper – 4 door

» 1,170mm (46") High-rise premium sleeper – 4 door
 » 1,320mm (52") Mid-rise premium sleeper – 4 door

» 1,320mm (52") High-rise premium sleeper – 4 door
 » 1,320mm (52") High-rise premium sleeper – 4 door

All standard sleepers have 4 access doors and vertical cab extenders.

\* Note additional sleeper options are available, speak with your Authorised Dealer.

## CAB (CONT.)

#### CAB INTERIOR

- » Overhead storage (up to 3 pockets based on cab configuration)
- » Rear Wall storage available (based on cab configuration)
- » Door Storage (2 pockets)
- » Cup Holders in dash
- » Centre storage console (available based on cab configuration)
- » Interior Trim pleated ultra leather or diamond plate
- » Central locking available
- » Power windows available (optional)
- » Self cancelling signals available (optional)
   » Internal grab handles

Speak with your Authorised Dealer for all options

#### SEATS

- » Driver: ISRI 'Big-Boy' air-ride Premium: 'MACK' embossed cloth trim, LH arm rest, upper, side and lower lumbar support with oscillating base and fore/aft seat cushion adjustment
- » Driver: ISRI 'Big-Boy' air-ride (optional): Cloth trim, upper, side and lower lumbar support with fore/aft seat cushion adjustment
- Passenger: ISRI fixed cushion
- Passenger: ISRI luxury air ride seat with upper and lower lumbar support, and fore/aft seat cushion adjustment (optional)

#### **STEERING WHEEL**

- » Bulldog soft touch rubber grip 457mm (18") diameter
- » Elite leather grip steering wheel (optional)
- » Adjustable tilt and telescopic steering column

#### INSTRUMENT

- » Driver information display: Co-Pilot
- » Speedometer/odometer (electronic)
- » Tachometer/hourmeter (electronic)
- » Voltmeter, engine hours, distance, trip recording
- » Engine coolant temperature, fuel and AdBlue levels
- Primary and secondary air pressure
   Oil pressure and oil temperature

#### FULL GAUGE PACKAGE INCLUDES

» Manifold pressure, transmission temperature, exhaust temperature, brake application pressure, front and rear drive axle temperature

#### WINDSCREEN WIPERS

- » Electronic variable-speed, intermittent wipers with washer
- » Reservoir mounted under bonnet

#### AUDIO SYSTEM

- » Premium Radio/CD player including hands free
- » iPod connector and USB connector

#### COMMUNICATIONS

- » GME CB radio (optional)
- » GME UHF radio (optional)

#### **CLIMATE CONTROL**

- » HVAC integral cab air conditioner/heater
- » Electronic controls
- » Replaceable dust intrusion filter

#### **COURTESY LAMPS**

» Drivers/Passengers door entry lighting
 » Ambient floor lighting

#### **SAFETY & WARNING**

- » Set of 3 safety warning triangles
- » Door mounted emergency procedure guide (optional)
- » Emergency eye wash bottle (optional)
- » 2.5kg in cab mounted fire extinguisher (optional)

#### TYRE EQUIPMENT

- » Wheel lug wrench kit
- » Bottle jack (optional)

#### **CAB EXTERIOR**

- » Fibreglass bonnet and polyfibre fenders with splash aprons
- » Bonnet tilts forward with spring assist
- » Chrome grille surround and side air intakes
- » Polished stainless steel cab skirts and air intake tubes
- » Black nylon bonnet hold down straps
- » Bright finish bonnet hold down straps (optional)
- » Stainless bug screen integrated with grille
- » Painted external sunvisor
   » Stainless steel exterior sunvisor (optional)

#### HEADLAMPS

» Hella integral light/indicator unit with polycarbonate lens

#### **MARKER & TAIL LAMPS**

- » 5 roof-mounted amber lights and 3 in 1 tail lamp
- » LED roof clearance and tail lamps (optional)

#### **REVERSING ALARM**

» Chassis mounted back up alarm (optional)

#### WARNING BEACON

- » Single amber revolving roof beacon (optional)
- » Double amber revolving roof beacons (optional)
- » Double amber revolving beacons air intake mounted (optional)
- » Beacons mounted on sleeper when a sleeper is selected

#### HOOK UP LAMP

» Rear of cab mounted hook up lamp (optional)

#### HORNS

- » 2 x roof mounted, air horn trumpets
- » 2 x under bonnet mounted, electric

#### MIRRORS

- » Heated 'West Coast' mirrors with stainless steel arms
- » LH and RH power mirrors (optional)
- » LH and RH 7" spotter mirrors
- » LH down mirror (optional)

#### WINDSCREEN STONE GUARD

» Matt black mesh windscreen stone guard (optional)

## PAINT & ACCESSORIES

#### PAINT TYPE & COLOUR

- » Cab/sleeper: Single non-metallic cab colour (Incredible white standard)
- » Chassis: Single non-metallic chassis colour (black standard)
- » Epoxy Mine specification primer (CA)

#### ACCESSORIES

» Additional factory fitted accessories are available, speak with your Authorised Dealer for full details.



## **GET THE TOTAL PACKAGE.**

Mack Genuine Parts are as tough as your truck. With premium materials and precision engineering, they're built to take whatever the road can throw at them.

Mack Total Support gives you the added confidence of warranties, servicing and maintenance from the people who made your machine.

Find more about Mack Total Support at macktrucks.com.au/parts-and-services/

Contact your dealer today and ask them to arrange for a Mack Driver Development Trainer to contact you.

**1300 MY MACK** 



#### macktrucks.com.au

#### **BORN READY.**

Trident-AB-05-12-2014 Printed in Australia

The information in this brochure was current at the time of publication. Mack Trucks reserves the right to make changes in specifications, equipment and design, or to discontinue models, options or extras without notice at any time. MACK and the Bulldog design are registered trademarks. All rights reserved. V-MAC is a registered trademark. All rights reserved.