## **22MY ISUZU D-MAX SPECIFICATIONS**

Engine	3.0L	1.9L
Series	Isuzu 4JJ3-TCX	RZ4E-TC
Description	3-litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)	1.9-litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)
Maximum torque	450Nm @ 1600→2600 rpm (automatic & manual)	350Nm @ 1800 $\rightarrow$ 2600 rpm (automatic and manual)
Maximum power	140kW @ 3600 rpm	110kW @ 3600 rpm
Bore x stroke	95.4mm x 104.9mm	80mm x 94.4mm
Displacement	2999cc	1898cc
Compression ratio	16.3:1	15.9: 1
Cylinder head	Isuzu-patent special aluminium alloy	Isuzu-patent special aluminium alloy
Valve gear	Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder	Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder
Induction	Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger	Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger
Cylinder block	Cast iron upper with induction-hardened cylinder bores, cast alloy lower	Cast iron upper with induction-hardened cylinder bores, cast alloy lower
Emission level	Euro 5	Euro 5
Alternator	90 amp with Intelligent Battery Sensor (IBS)	90 amp with Intelligent Battery Sensor (IBS)

#### **Transmissions**

Manual	275mm diameter 1.9L Engine: Isuzu	clutch plate and MVL-6Y 6-spee	dual mass flywhee	el n torque capacity	and output reduction	
Automatic	with fuel-saving lo	ck-up torque co	nverter on gears 3,	4, 5 and 6	ectronically controllecents, selects gear	
	descents to hold			Ü		,
Ratios: 1	3.0L Turbo  1st 2nd 3rd 4th 5th 6th Reverse	6-speed Manual 4.942 2.452 1.428 1.000 0.749 0.634 4.597	6-speed Automatic 3.600 2.090 1.488 1.000 0.687 0.580 3.732	1.9L Turbo  1st 2nd 3rd 4th 5th 6th Reverse	6-speed Manual 4.942 2.686 1.527 1.000 0.749 0.634 4.597	6-speed Automatic 3.600 2.090 1.488 1.000 0.687 0.580 3.732
Final drive	4x2 4x4	3.727 3.727	3.727 3.727	4x2	4.100 -	4.100 -
	Snorkelled diff bre	athers to increas	se fording depth an	d reduce mud blo	ockage	
Transfer gearing	4x4 low-range 4x4 high-range	2.482 1.000	2.482 1.000			
4x4 system	"Terrain Command rear differential loc		'shift on the fly' 2-l	nigh↔4-high sele	ction at up to 100kr	m/h, 4-low with
Drivetrain system	TCS (Traction Con-	trol System) on	all model variants			

#### **Steering**

Electric power steering with speed-sensing steering feel (light at low speed, heavy at high speed); tilt and telescopic adjustable steering wheel

Engine-speed-sensitive variable capacity Electric power system; 3.84 turns lock-to-lock via tilt-adjustable steering wheel

#### **Chassis**

Separate, full-length heavy-duty chassis with 8 cross members on all models

#### Front suspension

Independent, high-ride, coil springs, gas shock absorbers, upper and lower wishbones, stabiliser bar

#### Rear suspension

LS-M and all Cab Chassis models: Heavy Duty alloy-steel overslung long-span semi-elliptic leaf springs; gas shock absorbers

4x2 and 4x4 models: Alloy-steel overslung long-span semi-elliptic leaf springs; gas shock absorbers

#### **Axles**

#### Front

Independent 4x4: fully floating with outer CV, inner double offset joints and equal length driveshafts. Rating: 1450kg

#### Rear

Rigid semi-floating banjo with hypoid final drive and dual tapered needle roller bearings. Rating: 1910kg

#### **Brakes**

Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD), Electronic Stability Control (ESC), Emergency Brake Assist (EBA), Traction Control System (TCS), Rollover Mitigation, Hill Start Assist (HSA), Hill Descent Control (HDC) and Trailer Sway Control (TSC)

320mm dia. ventilated front discs with 2-piston calipers. 295mm rear drums

Power-assisted via 10" servo unit; central pull up park brake

#### **Wheels and Tyres**

SX	17" x 7" drilled silver-finish steel; 255 / 65 R17 All-Terrain
LS-M	17" x 7" alloy; 255 / 65 R17 All-Terrain
LS-U and LS-U+	18" x 7.5" alloy; 265 / 60 R18 Highway-Terrain
X-TERRAIN	18" x 7.5" dark grey alloy; 265 / 60 R18 Highway-Terrain
All Models	Full size steel spare wheel

#### **Service Plus**

Ro As Ca Pri	Warranty	For the ultimate peace of mind, every Isuzu D-MAX comes standard with a comprehensive, bumper-to-bumper 6 years/150,000km warranty^.
	Roadside Assistance	Enjoy up to 7 years Roadside Assistance <sup>&lt;</sup> when you complete your scheduled services at a Participating Isuzu UTE Dealer.
	Capped Price Servicing	As an owner you will get access to our Capped Price Servicing Program. The CPS Program covers the first 7 Scheduled Services in line with the Scheduled Service Intervals.

"6 years/150,000km (whichever occurs first), for Isuzu UTE Vehicles with a Warranty Start Date on or after 1/1/19. Excludes trays & accessories. "The Roadside Assistance Program" ("RSA Program") provides Coverage to RSA Eligible Vehicles with a Warranty Start Date on or after 1/9/20 for a maximum of 7 years (unlimited kilometres) Initial 13 months Coverage provided from the Warranty Start Date. The Coverage will be reset for another 13 months from each date that a Participating Isuzu UTE Dealer conducts a Scheduled Service on the vehicle. For full terms & conditions visit isuzuute.com.au/roadside-assistance-disclaimer. "The Capped Price Servicing Program" applies to CPS Eligible Vehicles at Participating Isuzu UTE Dealers only. For 19MY & later vehicle models, the Capped Price Servicing covers the first 7 Scheduled Services for up to 7 years/105,000km (whichever occurs first). CPS Program is subject to change. For full terms & conditions, current pricing & model eligibility visit isuzuute.com.au/service-plus-disclaimer.

#### Safety

IDAS	Every D-MAX comes with Isuzu's Intelligent Driver Assistance System (IDAS") built-in to protect and enhance the driving experience. IDAS includes smart technologies as well as other passive and active safety features.

\*IDAS features are designed to assist the driver, but should not be relied upon nor used as a substitute for safe driving practices. Feature operation may vary in different driving conditions. For full explanation of limitations, see Owner's & Driver's Manual.

ANCAP	The entire D-MAX range has achieved
RATING	a maximum 5-star ANCAP safety
	rating in 2020.

\*Limited stock available on these models. Please contact your local Isuzu UTE Dealer for more information.

SPECIFICATIONS	4x2 High-Ride						4x4⁺												
	Single Cab	Space Cab	Crew Cab	Crew	Crew	Single Cab	Space Cab	Space	Crew Cab		Crew Cab	Crew	Crew Cab	Crew	Crew	Crew			
	Chassis <b>SX</b>	Chassis <b>SX</b>	Chassis SX	Cab Ute <b>SX</b>	Cab Ute LS-U	Chassis <b>SX</b>	Chassis <b>SX</b>	Cab Ute	Chassis SX	Cab Ute SX	Chassis LS-M	Cab Ute <b>LS-M</b>	Chassis LS-U	Cab Ute LS-U	Cab Ute	Cab Uto X-TERRA			
Engine																			
1898cc DOHC 4cyl. with intercooled turbocharger (350Nm, 110kW)	•																		
2999cc DOHC 4cyl. with intercooled turbocharger (450Nm, 140kW)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
Transmissions																			
6-speed manual transmission	•					•	•		•			•		•					
6-speed "Rev-Tronic" automatic transmission with sequential sport mode	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
Safety and Security																			
4-channel 4-sensor Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD)						•													
Electronic Stability Control (ESC)																			
Traction Control System (TCS)																			
Emergency Brake Assist (EBA)																			
Hill Start Assist (HSA)																			
Hill Descent Control (HDC)																			
Autonomous Emergency Braking (AEB)																			
Turn Assist with AEB					•														
Post-Collision Braking																•			
Forward Collision Warning (FCW)					•														
Misacceleration Mitigation (*AT models only)	•*	•	•	•	•	•*	•*	•	•*	•	•	•*		•*		•			
Adaptive Cruise Control (ACC) with Stop and Go functionality (*AT models only)	*	•		•		•*	•*		•*	•		•*		•*		•			
Traffic Sign Recognition (TSR)		•		•	•	•	•	•		•	•					•			
Intelligent Speed Limiter		•		•	•	•		•		•									
Manual Speed Limiter																			
Lane Departure Warning (LDW)																			
Lane Departure Prevention (LDP)																			
Lane Keep Assist (LKA) (*AT models only)	•*	•		•	•	•*	*	•	•*	•	•	•*		•*					
Emergency Lane Keeping (ELK)		•			•						•								
Lane Support System (LSS) Switch (disables LDW, LDP, LKA, ELK)																			
Driver Attention Assist																			
Blind Spot Monitoring (BSM)		•	•	•	•	•	•	•		•	•					•			
Rear Cross Traffic Alert (RCTA)		•		•	•	•	•	•	•	•	•					•			
Reversing camera		•		•		•			•	•									
Rear parking sensors								•											
Front parking sensors																•			
8 Airbags: dual front, curtain, side, driver's knee and far side airbags		•	•	•	•	•	•	•	•	•	•		•	•	•	•			
Passenger side SRS airbag on/off switch								•	•							•			
Height-adjustable upper mounts for front seat belts		•		•		•			•	•									
Pre-tensioners with load limiters for front seat belts		•		•		•			•	•									
Pre-tensioners with load limiters for outer rear seat belts			•	•	•	_			•	•	•					•			
3-point retractable seat belts for all rear and centre seating positions				•	•					•						•			
Intelligent seatbelt reminder (all seats)	•	•				•	•	•	•							•			
2 childseat tethers and ISO FIX compatible anchor points			•	•	•				•	•	•				•	•			
Height-adjustable head restraints for full-size seats		•	•	•	•		•	•	•	•	•	•		•	•	•			
Integrated head restraint on front seats	•					•				-						_			
Child-proof rear door locks			•	•	•				•	•	•	•	•	•	•	•			
Single 10 inch servo brake master cylinder	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•			
Side anti-intrusion bars inside all doors	•	•	•	•	•	•	•	•	•	•	•				•	•			
Engine immobilizer		•	•	•	•	•	•	•	•	•	•				•	•			
Rear window demister		•	•	•		-	•	•	•		•					•			
High Density Polyethylene (HDPE) fuel tank	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•			
High mount brake light on cabin	•	•	•	•	•	•	•	•	•	•	•	•			•	•			
Dual horn	•	•	•	•	•	•	•	•	•	•	•				•	•			
Protection		-	-			-	-	-	-	-	-		_	_					
			_				_							_					
Under-front steel skid plate	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
Steel plate guards: sump, transfer case, fuel tank leading edge; reinforced resin under fuel tank						•	•	•	•	•	•	•	•	•	•	•			
Suspension and Brakes																			
Standard rear leaf suspension				•	•			•		•				•	•	•			
Heavy duty rear leaf suspension	•	•	•			•	•		•		•	•	•						
Front independent, coil spring suspension w/gas shock absorbers, upper and lower wishbones and stabilise	r bar •	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
Heavy-duty brakes: 320mm ventilated front discs w/twin-pot calipers, 295mm rear drums	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			

## SPECIFICATIONS

SPECIFICATIONS		4x	2 High-F	Ride							4x4+					
	Single Cab	Space Cab	Crew			Single Cab	Space	_			Crew		Crew			_
	Cab Chassis <b>SX</b>	Cab Chassis <b>SX</b>	Cab Chassis <b>SX</b>	Crew Cab Ute <b>SX</b>	Crew Cab Ute LS-U	Cab Chassis <b>SX</b>	Čab Chassis <b>SX</b>	Space Cab Ute LS-U		Crew Cab Ute SX	Cab Chassis <b>LS-M</b>	Crew Cab Ute <b>LS-M</b>	Cab Chassis LS-U	Crew Cab Ute <b>LS-U</b>		Crew Cab Ute X-TERRAIN
In-cabin Storage	3/	3/	3/	3/	L3-U	3/	3/	L3-U	3/	3/	L3-IVI	LS-IVI	L3-U	L3-U	L3-U+	A-TENNAIN
Lower glovebox compartment only	•	•	•	•		•	•		•	•						
Upper and lower glovebox compartments					•	_		•			•	•	•	•	•	•
Power outlet in lower instrument panel	•	•	•	•	•	•	•	•	•	•	•	•		•		•
Centre floor console	•	•			•	•	•	•	•	•						•
Dual-purpose driver and front passenger cup holder tray	•								•							•
Rear passenger door cup holders			•	•	•				•	•	•	•		•	•	•
Pockets on backs of front seats					•			•		-	•	•	•	•		•
Overhead console with twin map lights and flip-down sunglasses case		•	•	•		•	•	•	•	•		•	•			
Front door storage compartment with bottle bulge								•		•			•			
2 coat hooks	_			•					•	•		•	•	•		•
Flip up convenience hook behind passenger front seat								•	•			•	•	•		
Tool storage behind rear seats		•	•	•	•		•	•	•	•	•	•	•	•		•
Tool storage behind front seats		•				•	•		•							
-																
Rear Tub																
Double-walled ute tub				•	•			•		•		•		•	•	•
4 cargo tie-down hooks inside ute tub				•	•			•		•		•		•	•	
Under rail tub liner					•			•						•	•	•
2 cargo tie-down hooks inside ute tub																•
Exterior Style																
Short front overhang for optimal manoeuvrability and approach angle	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Halogen multi-reflector project lens headlights for extra low beam depth and reduced flare				•					•		_	_	_			
Bi-LED headlights with auto-levelling function					•			•	•		•	•	•	•	•	•
Automatic headlights		•	•	•	•	•	•	•	•	•	•	•	•	•		
Automatic high beam		•		•		•	•	•		•		•		•		
Coming home light										•						
Welcome light				•					•	•		•				
LED Daytime Running Lights (DRLs)																
LED fog lights																
Matte grey radiator grille									•				·	•		•
Chrome radiator grille				•		•	•		•	•		•				
Dark grey radiator grille					•											
Colour-coded front bumper																
Integrated Rear Step Bumper (Colour-coded)			•			•	•				•		•			
Rear Bumper (Black)				•	_							_				•
Factory fitted tow bar receiver		_	•			•	•		•		_					
Space cab rear "wing" doors					_								_			
Aluminium side steps		•					•									
Dark grey side steps					•								_			
Black door and tailgate handles																•
Colour-coded door and tailgate handles	_	•	•	•			•		•	•						
Chrome door and tailgate handles											•	•				
Dark grey door and tailgate handles					_			•					_			
Lockable tailgate																
Aero sports bar				•				•		•		•				
Matte black roller tonneau																
Front and rear underbody spoilers  Dark grey fender flares																
Black roof rails																
Black power door mirrors				_						_						•
	•	•	•	•		•	•		•	•						
Colour-coded power door mirrors with integrated turn indicators											•	•				
Chrome fold-in power door mirrors with integrated turn indicators					•			•					•	•	•	
Dark grey fold-in power door mirrors with integrated turn indicators																•
Heated door mirrors																
Centre front roof-mounted bee-sting aerial	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
LED rear combination lamps					•			•					•	•	•	

<b>SPECIFIC</b>	ATI	ONS
-----------------	-----	-----

SPECIFICATIONS		4x2	2 High-F	Ride		4x4*										
3PECIFICATION3																
	Single	Space Cab	Crew			Single Cab	Space Cab				Crew		Crew			
	Cab Chassis	Cab Chassis	Cab Chassis	Crew Cab Ute	Crew Cab Ute	Cab Chassis	Cab Chassis	Space Cab Ute	Crew Cab Chassis	Crew Cab Ute	Cab Chassis	Crew Cab Ute	Cab Chassis	Crew Cab Ute	Crew Cab Ute	Crew Cab Ute
	SX	SX	SX	SX	LS-U	SX	SX	LS-U	SX	SX	LS-M	LS-M	LS-U	LS-U		X-TERRAIN
Seating	0,1	0,1	071	0,1	20 0	0,1	0,1		0,1	071	20	20		200	20 0.	7. 12.00
Front bucket whiplash protection seats	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
6-way adjustable driver seat	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
8-way electric adjustable driver seat															•	•
Electric adjustable lumbar support (driver seat only)					•			•					•	•	•	•
Heated front seats															•	•
Split-fold rear seat			•	•					•	•						
Split-fold rear seat with centre arm rest					•						•	•	•	•	•	•
Rear centre seat headrest			•	•	•				•	•	•	•	•	•	•	•
Cabin Amenities																
Dual zone climate control air-conditioning with integrated heater/demister					•			•					•	•	•	•
Manual air-conditioning with integrated heater/demister	•	•	•	•		•	•		•	•	•	•				
Rear seat air-conditioning vents			•	•	•				•	•	•	•	•	•	•	•
Pollen and fine particle air filter	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Power windows with one-touch up/down driver's window with safety stop and delay closing	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Comfort turn signal	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Central locking with keyless entry	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Smart keyless entry					•			•					•	•	•	•
Walk away lock					•			•					•	•	•	•
Push button start					•			•					•	•	•	•
Remote engine start																•
Power-adjustable door mirrors with turn indicator lights					•			•			•	•	•	•	•	•
Power-adjustable door mirrors	•	•	•	•		•	•		•	•						
4 speaker sound system	•	•	•	•		•	•		•	•						
6 speaker sound system								•			•	•	_			
"Sky Sound" roof-mounted sound system with 8 speakers (mounted in front dash, front doors, rear doors and roof)					•								•	•	•	•
9 inch touchscreen display with Apple CarPlay® and Android Auto™					•	_		•			_		•	•	•	•
7 inch touchscreen display with Apple CarPlay® and Android Auto™	•	•	•	•	_	•	•	_	•	•	•	•		_	_	
Built-in satellite navigation with MID turn-by-turn directions					•			•			_	_	•	•	•	•
Rear centre console USB charging port					•						•	•	•	•	•	•
Tilt and telescopic adjustable steering wheel with electric power steering		•		•	•			•	•			•	•	•	•	•
Urethane steering wheel with cruise, audio and voice recognition controls  Leather steering wheel with cruise, audio and voice recognition controls		•	•	•		•	•		•	•	•	•				
Smart MID with digital speedometer, safety information, fuel economy and range, odometer, trip					•			•					•	•	•	•
information and service reminder	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Electro-luminescent gauges	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
"Terrain Command" 4x4 select dial						•	•	•	•	•	•	•	•	•	•	•
Rear differential lock button						•	•	•	•	•	•	•	•	•	•	•
Automatic windshield wipers	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Intuitive flat wiper blade					•			•					•	•	•	•
Day/night interior rear view mirror	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Auto-dimming rear view mirror					•			•					•	•	•	•
Sun visors with vanity mirrors (driver and passenger) and ticket retaining strap (driver)					•			•					•	•		
Sun visors with illuminated vanity mirrors (driver and passenger) and ticket retaining strap (driver)															•	•
Fixed A-pillar assist-grips for driver and front passenger	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Fixed B-pillar assist-grips for rear passengers				•	•				•	•	•	•	•	•	•	•
Folding assist-grips for driver and front passenger				•	•				•	•	•	•	•	•	•	•
Folding assist-grips for rear passengers				•	•				•	•	•	•	•	•	•	•
Carpet flooring					•			•					•	•	•	•
Easy-clean vinyl flooring									_							

<b>FUEL, WEIGHTS</b>		4x2 Hi	gh-Ride								4x4+					
	Single	Space	Crew			Single	Space				Crew		Crew			
AND DIMENSIONS	Cab Chassis SX	Cab Chassis SX	Cab Chassis	Crew Cab Ute <b>SX</b>	Crew Cab Ute <b>LS-U</b>	Cab Chassis <b>SX</b>	Cab Chassis SX	Space Cab Ute LS-U	Crew Cab Chassis SX	Crew Cab Ute <b>SX</b>	Cab Chassis	Crew Cab Ute <b>LS-M</b>	Cab Chassis	Crew Cab Ute <b>LS-U</b>	Crew Cab Ute LS-U+	Crew Cab Ute X-TERRAIN
D-MAX ADR 81/02 <sup>△</sup> Fuel Consumption Values	1.9L 3.0L															
Transmission (MT = Manual, AT = Automatic)	MT/AT MT/AT	AT	AT	AT	AT	MT / AT	MT / AT	AT	MT / AT	AT	AT	MT / AT	AT	MT / AT	AT	AT
FUEL CONSUMPTION (litres/100km)																
Combined	7.0 8.0	8.0	8.0	7.7	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.7/8.0	8.0	7.7/8.0	8.0	8.0
Urban	8.1/7.9 10.2/9.8	9.8	9.8	9.5	9.8	10.2/9.8	10.2/9.8	9.8	10.2/9.8	9.8	9.8	9.7/9.8	9.8	9.7/9.8	9.8	9.8
Extra Urban	6.5/6.6 6.7/6.9	6.9	6.9	6.7	6.9	6.7/6.9	6.7/6.9	6.9	6.7/6.9	6.9	6.9	6.6/6.9	6.9	6.6/6.9	6.9	6.9
CO <sup>2</sup> (g/km)																
Combined	183/184 206/207	207	207	200	207	206/207	206/207	207	206/207	207	207	200/207	207	200/207	207	207
Urban	212/208 262/254	254	254	246	254	262/254	262/254	254	262/254	254	254	251/254	254	251/254	254	254
Extra Urban	170/174 174/180	180	180	174	180	174/180	174/180	180	174/180	180	180	171/180	180	171/180	180	180
Dimensions (mm unless stated otherwise)																
Wheelbase	3125	3125	3125	3125	3125	3125	3125	3125	3125	3125	3125	3125	3125	3125	3125	3125
Overall length	5325	5285	5285	5265	5270	5325	5285	5270	5285	5265	5285	5265	5285	5270	5270	5303
Overall width (excluding door mirrors)	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1880
Overall height (*depends on body fitted)	1790*	1800*	1800*	1785	1790	1790*	1800*	1790	1800*	1785	1800*	1785	1805*	1790	1790	1810
Front overhang	890	890	890	890	890	890	890	890	890	890	890	890	890	890	890	905
Rear overhang (*depends on body fitted)	1310*	1270*	1270*	1250	1250	1310*	1270*	1250	1270*	1250	1270*	1250	1270*	1250	1250	1250
Wheel track width	1570	1570	1570	1570	1570	1570	1570	1570	1570	1570	1570	1570	1570	1570	1570	1570
Ground clearance	235	235	235	235	240	235	235	240	235	235	235	235	240	240	240	240
Turning circle diameter between kerbs (metres)	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5
Approach angle	29.6°	29.6°	29.6°	30°	30.5°	29.6°	29.6°	30.5°	29.6°	30°	29.6°	30°	30°	30.5°	30.5°	30.5°
Departure angle	24.6°	25.3°	25.3°	23.9°	19.0°	24.6°	25.3°	19.0°	25.3°	23.9°	25.3°	23.9°	20.6°	19.0°	19.0°	19.0°
Ramp-over angle	23.9°	23.9°	23.9°	23.3°	23.8°	23.9°	23.9°	23.8°	23.9°	23.3°	23.3°	23.3°	24.3°	23.8°	23.8°	23.8°
Load area (mm)																
Cab to rear axle	1240	765	450	450	450	1240	765	765	450	450	450	450	450	450	450	450
Length (top)	-	-	-	1495	1495	-	-	1805	-	1495	-	1495	-	1495	1495	1495
Length (floor ) (*inside genuine accessory tray body)	2550*	2100*	1800*	1570	1570	2550*	2100*	1835	1800*	1570	1800*	1570	1800*	1570	1570	1570
Maximum width (*inside genuine accessory alloy tray body)	1777*	1777*	1777*	1530	1530	1777*	1777*	1530	1777*	1530	1777*	1530	1777*	1530	1530	1530
Width between wheel houses	-	-	-	1122	1122	-	-	1122	-	1122	-	1122	-	1122	1122	1122
Depth	-	-	-	490	490	-	-	490	-	490	-	490	-	490	490	490
Interior (mm)																
Leg room - front	1075	1075	1075	1075	1075	1075	1075	1075	1075	1075	1075	1075	1075	1075	1075	1075
Leg room - rear	-	-	905	905	905	-	-	-	905	905	905	905	905	905	905	905
Shoulder room - front	1460	1460	1460	1460	1460	1460	1460	1460	1460	1460	1460	1460	1460	1460	1460	1460
Head room - front	1020	1020	1020	1020	1020	1020	1020	1020	1020	1020	1020	1020	1020	1020	1020	1020
Rear cargo space	-	730	-	-	-	-	730	730	-	-	-	-	-	-	-	-
Mass (kg)																
Gross Vehicle Mass (GVM)	3000 3000	3000	3000	3000	3000	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100
Kerb weight <sup>^</sup>	1595/1620 1695/1700	1770	1825	1945	2015	1780/1790	1850/1860	2060	1900/1910	2035	1905	2020/2030	1960	2100/2105	2112	2165
Payload <sup>-</sup> (cab chassis models: final mass depends on body fitted)	1405/1380 1305/1300	1230	1175	1055	985	1320/1310	1250/1240	1040	1200/1190	1065	1195	1080/1070	1140	1000/995	988	935
Gross Combination Mass (GCM)	5300/5500 5850	5850	5850	5850	5850	6000	6000	6000	6000	6000	6000	5950	6000	6000	6000	6000
Maximum towing mass (braked trailer)	2800/3000 3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500	3500
Maximum towing mass (non-braked trailer)	750 750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750
Maximum tow ball download (when fitted with genuine Isuzu UTE tow kit)	280/300 350	350	350	350	350	350	350	350	350	350	350	350	350	350	350	350
Fuel tank capacity (litres)	76 76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76

<sup>&</sup>lt;sup>4</sup>Fuel consumption & emissions figures based on ADR 81/02 & are to be used for vehicle comparison purposes only. Actual fuel consumption & emissions will vary depending on many factors including, but not limited to, traffic conditions, individual driving style & vehicle condition.

^Kerb weight - unladen mass of vehicle & full tank of fuel, excludes tray body for cab chassis vehicles. Fuel weight ratio is based on Fuel Standard (Automotive Diesel) Determination 2001. \*Payload equals GVM minus kerb weight. \*Limited stock available on these models. Please contact your local Isuzu UTE Dealer for more information.

# CAB CHASSIS BODY STYLES AND DIMENSIONS (22MY)



SX Single Cab Chassis 4x2 & 4x4



SX Space Cab Chassis 4x2 & 4x4



SX Crew Cab Chassis 4x2 & 4x4





LS-M Crew Cab Chassis 4x4












































# **CAB CHASSIS AND UTE BODY STYLES AND DIMENSIONS (22MY)**




LS-U Crew Cab Chassis 4x4














SX Crew Cab Ute 4x2 & 4x4














LS-M Crew Cab Ute 4x4











# UTE BODY STYLES AND DIMENSIONS (22MY)




LS-U Space Cab Ute 4x4













LS-U Crew Cab Ute 4x2 & 4x4 LS-U+ Crew Cab Ute 4x4














X-TERRAIN Crew Cab Ute 4x4









# **COLOURS AND TRIM (22MY)**

## **Body Colours**



**Basalt Black mica** 



**Cobalt Blue mica** 



**Mercury Silver metallic** 



**Obsidian Grey mica** 



**Mineral White** 



Marble White pearl
(LS-U Range & X-TERRAIN Exclusive)



Magnetic Red mica
(LS-U Range & X-TERRAIN Exclusive)



Volcanic Amber metallic (X-TERRAIN Exclusive)

### **Interior Trim**



Standard Black Cloth (On SX models)

High Grade Cloth
(On LS-M & LS-U models)

Leather Accented<sup>†</sup>
(On LS-U+)

Leather Accented' with Red Stitching (On X-TERRAIN)

## **TRAY STYLES**

### **Economy Alloy**



**General Purpose Alloy** 



**Heavy Duty Alloy** 



**Heavy Duty Steel** 



**Mine Specification Steel** 



Single



































