

Industry	Logistics	
Market	RHD Market	
GVM (kg)	4,500kg / 6,000 Kg	
Curb Weight (kg)	≤2500	
Dimensions (mm)	5960*1950*2260	
Wheel Base (mm)	3360	
Cabin	Cabin Model	1880 Width / Single Cabin
Performance	Platform	ELE4
	Working condition	Hill / Plain
	Altitude	≤1800m (Less than 2000m)
	Climatic conditions	General
	Environment Temp (°C)	Up to 45°C Lowest -15°C
	Applicable road conditions	High-grade highway
	Maximum speed	95km/h
Maximum gradient	21%	
Power and accessory system	Battery	Technical route: LFP Brand: CATL Battery capacity(kWh): 81.14 (Optional 100) Energy density (wh/kg): 146.7 Liquid cooling
	Motor	Rated/peak power: 64/150 Peak torque/peak rotate speed (Nm/rpm): 300/12000 Type: Single reduction motor
	Cooling system	Electric fan Auxiliary water tank
	Frame	Frame structure Vertical beam section
Front Axle	Front axle type Payload (Front axle)(t)	Forged I-beam 2.4T
Rear Axle	Rear axle type Rear Payload (Rear axle) (t)	Integral type (stamped axle housing) 4.5T
Battery	60Ah, 2 sets Maintenance-free battery; Battery cover; Main power switch	
Brake	Braking type	Hydraulic auxiliary brake
	Brake gap automatic adjustment arm	
	Brake type	Front discs and rear drum
	Brake safety features	ABS+EBD / ESC / TCS / HSA / BA
Parking brake	Central drum brake	
Suspension	Front suspension system	Number of leaf springs: 3 Front stabilizer bar
	Rear suspension	Number of leaf springs: 5+2 Rear stabilizer bar
Steering	Electric steering Multifunction steering wheel	With bluetooth
Tray	Tray Size (mm*mm*mm)	Cab Chassis Only
Tyre	205/75 R17.5 Spare Tyre: Yes / Rim material: Yes /Alloy	
Tools		
Cabin	Cab type	Fully tilts for maintenance access
	Air deflector	Optional
	Body color	Metallic Painting
	Doors and windows	Power
	Windshield	Colorless laminated glass
	Rear window glass	Colorless area tempered
	Door lock	Central control/ electric door lock
		Multi-gear intermittent smooth
	Wiper	Windshield wiper / Water spray
	Audio	MP5 (MP5+Radio+USB+AUX+Reversing Image)
Air conditioner	Model	Integrated heating and cooling
	Control	Electric
Safety	Unclosed door warning	
	Warning if cabin tilt mechanism not correctly locked	
	Key alarm device	
	VSP (Low Speed Pedestrian Warning System)	
	Rear lower guard / Side guard	
	Reversing radar / Reverse image / Reversing buzzing	
Charging	Fast and Slow Charge	Slow Charge around : 12-14 hours Fast Charge around: 1.5 hours



Specification may change without notice.