



FX - 209 ROTARY CUTTER

Versatile 9' Rigid Deck Mower

- Rigid single domed 7 gauge deck construction
- Two rotor base unit common to all configuration
- Pull type and three point
- 540 and 1000 RPM drive options
- 9ft / 3m overall width
- Heavy duty gear boxes and G8 drive lines
- Pull type unit has the ability to accept open clevis, solid tongue, adjustable clevis or precision hitch options
- Four tire options: solid laminate, severe duty, severe duty foam filled or forklift tires
- 1/4" x 4" deck protection ring to guard against blade to deck damage



World Class *Built to Last*

schulte.ca

FX-209 Specifications

SPECIFICATIONS

Overall Width
Overall Length
Transport Clearance
Cutting Height
Cutting Width
Cutting Capacity
Approximate Weight

Hitch Type
Deck Thickness
Side Skirt
Gear Box Rating
Blade Tip Speed
Blade Overlap
Tractor PTO Speed
Minimum Tractor HP
Deflectors
Deck Protection Rings


FX-209

116.5" (2.96 m) Skids Inboard 120.5" (3.06 m) Skids Outboard
162.5" (4.1 m) Trailing Unit, 127" (3.3 m), 3 Point / Semi Mount Swing / Semi Mount
11.5" (29.2 cm)
2" - 13" (5.1 cm - 33 cm)
109.25" (2.78 m)
3" (7.6 cm)
2400 lbs (1088 kg) Trailing, 2300 lbs (1043 kg) 3 Point, 2100 lbs (952 kg) Semi Mount
2860 lbs (1297 kg) Semi Mount Swing
Cat. II & III 3 Point / Trailing Pull
7 GA (3/16", 4.6 mm)
1/4" x 13.75" (6.35 mm x 337 mm)
Outboard 210 HP (157 kW)
540 RPM - 17086 FPM 1000 RPM - 17355 FPM
4.75" (121 mm)
540 or 1000 RPM
50 HP (37.3 kW)
Double chain front and rear
1/4" X 4"




Stump Jumpers

Deck Protection Rings



Moveable Skid Shoes / Safety Chains



Trailing Hitch



Three Point Hitch

OPTIONS - FX-209

• 3pt hitch • Trailing hitch • Standard clevis
• Adjustable clevis • Solid tongue • Precision hitch
• Laminate tires • Severe Duty tires • Severe
duty foam filled tires • Forklift tires • Hydraulic or
Non hydraulic rear wheel beam • Pans with Schulte
super suction blades • 1/2 length front and rear
safety belting



Open Clevis Hitch



Adjustable Clevis



Solid Tongue Hitch



Precision Hitch

SCHULTE

Schulte Industries Ltd.

PO Box 70, Englefeld, SK Canada S0K 1N0

Ph (306) 287-3715 Fx (306) 287-3355

Email info@schulte.ca Web www.schulte.ca



Sold By:

Schulte is a registered trademark of Alamo Group Inc.

Schulte Industries Ltd. reserves the right to change the design and specifications of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.

Printed in Canada

Prepared by NELSON GRAPHIC DESIGN

201907

