



## G X - 1 5 0   R O T A R Y   C U T T E R

- 1** A single domed 10ga continuously welded deck makes the cutter extremely easy to clean, prevents water pooling, rusting and helps shed debris
- 2** An 80° CV shaft allows for smooth power transmission during tight turns. The "Best in Class" drive system features a category 6 CV for 540rpm and the 1000 rpm is a category 5. The drive line on the cutter itself employs self-adjusting friction clutches to protect your investment and always operate at peak performance
- 3** Equipped with Schulte Super Suction Blades with 6.5 " blade overlap for maximum grass lift and cut
- 4** A four gearbox drive line with independent slip clutches
- 5** Deck protection rings are standard and protect the cutter deck from rising blades
- 6** Deep 13 5/8" deck combined with high blade tip speeds, provides a faster cut rate than competitors.
- 7** High flex wing working range of 25° down to 90° up



**World Class** *Built to Last*

[schulte.ca](http://schulte.ca)

# Specifications

## SPECIFICATIONS

Cutting Width	15' (4.57m)
Overall Width	15.8' (4.83m)
Overall Length	16.8' (5.13m)
Cutting Height	1.75"-16.75" (45mm-425mm)
Transport Width	93" (2.36m)
Transport Height	84" (2.13m)
Weight (Depends on Config.)	5,050lbs (2291kg)
Hitch Weight	1,520lbs (689kg)
Cutting Capacity	3.5" (89mm)
Minimum Tractor Size	50hp (37kw)
Blade Tip Speed	540rpm
Center	16,286 ft/min (4964m/min)
Wing	15,459 ft/min (4711m/min)
Blade Tip Speed	1000rpm
Center	16,390 ft/min (4996m/min)
Wing	15,708 ft/min (4788m/min)
Blade Overlap	6.5" (165mm)
Divider Gearbox Rating	260hp (194kw)
Center & Wing Gearbox Rating	210hp (155kw)*
540 CV	Cat 6
1000 CV	Cat 5
Wing Drive Shafts	Cat 5
Deck Thickness	.135" (10ga or 3.4mm)
Side Skirt Depth & Thickness	13.6" (346mm) 1/4" (6.4mm)
Wing Working Range	25° down to 90° up
Wing Floating Range	25° down to 30° up



### GX-150

Continuously Welded  
Single Domed Deck




Laminated Tires



Solid tongue or Pro Level Hitch (shown)  
Fits Cat 2 and Cat 3 Hitches



Fork Lift Tires



Deck protection rings  
are standard



Heavy duty cast hinge line  
with wiper seals



Gearbox Sight Glass



Heavy duty 3/4" thick blade disc with  
4" blades and pentagon blade bolts

## GX-150 Features and Options

- Solid laminated tires 20" or 26" • Forklift or laminated tires • 4, 6 or 8 tire options • Safety light kit • Pro Level hitch or solid tongue • Leveling rod (optional addition of second tension link)
- 540 or 1000 RPM Drive package • Single or double chains front and rear • Gearbox sight glass



Narrow transport over-centering  
wing design

# SCHULTE

**Schulte Industries Ltd.**

PO Box 70, Englefeld, SK Canada S0K 1N0

Ph (306) 287-3715 Fx (306) 287-3355

Email [info@schulte.ca](mailto:info@schulte.ca) Web [www.schulte.ca](http://www.schulte.ca)



Sold By:

Schulte is a registered trademark of Alamo Group Inc.

Schulte Industries Ltd. reserves the right to change the design and specifications of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.

Printed in Canada

20106/15

