



G X - 1 3 0 R O T A R Y C U T T E R

- 1** A single domed 10ga continuously welded deck makes the cutter extremely easy to clean, prevents water pooling, rusting and helps shed debris
- 2** An 80° CV shaft allows for smooth power transmission during tight turns. The "Best in Class" drive system features a category 6 CV for 540rpm. The drive line on the cutter itself employs self-adjusting friction clutches to protect your investment and always operate at peak performance
- 3** Equipped with Schulte Super Suction Blades with 6.5 " blade overlap for maximum grass lift and cut
- 4** A four gearbox drive line with independent slip clutches
- 5** Deck protection rings are standard and protect the cutter deck from rising blades
- 6** Deep 13 5/8" deck combined with high blade tip speeds, provides a faster cut rate than competitors
- 7** High flex wing working range of 25° down to 90° up



World Class *Built to Last*


schulte.ca

Specifications




SPECIFICATIONS

	GX-130
Cutting Width	13' (3.96m)
Overall Width	13.8' (4.22m)
Overall Length	16.8' (5.13m)
Cutting Height	1.75"-16.75" (45mm-425mm)
Transport Width	93" (2.36m)
Transport Height	72" (1.83m)
Weight (Depends on Config.)	4725 Lbs (2143 kg)
Hitch Weight	1420 lbs (644 kg)
Cutting Capacity	2.5" (89mm)
Minimum Tractor Size	45hp (36kw)
Blade Tip Speed	540rpm
Center	16286 ft/min (4964 m/min)
Wing	16031 ft/min (4886 m/min)
Blade Overlap	6.5" (165mm)
Divider Gearbox Rating	250hp (186kw)
Center & Wing Gearbox Rating	130hp (97kw)*
540 CV	Cat 6
Wing Drive Shafts	Cat 5
Deck Thickness	.135" (10ga or 3.4mm)
Side Skirt Depth & Thickness	13.6" (346mm) 1/4" (6.4mm)
Wing Working Range	25° down to 90° up
Wing Floating Range	25° down to 30° up



Pro Level Hitch Fits Cat 2 and Cat 3 Hitches, or solid tongue hitch



Laminated Tires



Fork Lift Tires



Deck protection rings are standard



Heavy duty cast hinge line with wiper seals



Continuously welded single domed deck



Heavy duty 3/4" thick blade disc with 4" blades and pentagon blade bolts

GX-130 Features and Options

- Solid laminated tires 20" or 26"
- Forklift tires • 4 or 6 tire options
- Safety light kit
- Pro Level or solid tongue hitch
- Leveling rod
- 540 RPM drive package
- Single chains (optional double chains) front and rear
- Through axles only



Narrow transport over-centering wing design



Schulte Industries Ltd.
 PO Box 70, Englefeld, SK Canada S0K 1N0
 Ph (306) 287-3715 Fx (306) 287-3355
 Email info@schulte.ca Web www.schulte.ca



ISO 9001

Sold By:

Printed in Canada

20106/15



Schulte is a registered trademark of Alamo Group Inc. Schulte Industries Ltd. reserves the right to change the design and specifications of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.