24MY ISUZU D-MAX SPECIFICATIONS

3.0L	1.9L
Isuzu 4JJ3-TCX	RZ4E-TC
3-litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)	1.9-litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD)
450Nm @ 1600→2600 rpm (automatic & manual)	350Nm @ 1800 \rightarrow 2600 rpm (automatic and manual)
140kW @ 3600 rpm	110kW @ 3600 rpm
95.4mm x 104.9mm	80mm x 94.4mm
2999cc	1898cc
16.3 : 1	15.9: 1
Isuzu-patent special aluminium alloy	Isuzu-patent special aluminium alloy
Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder	Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder
Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger	Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger
Cast iron upper with induction-hardened cylinder bores, cast alloy lower	Cast iron upper with induction-hardened cylinder bores, cast alloy lower
Euro 5	Euro 5
90 amp with Intelligent Battery Sensor (IBS)	90 amp with Intelligent Battery Sensor (IBS)
	Isuzu 4JJ3-TCX 3-litre turbo-diesel, in-line 4-cylinder, DOHC, 16-valve with Diesel Particulate Diffuser (DPD) 450Nm @ 1600→2600 rpm (automatic & manual) 140kW @ 3600 rpm 95.4mm x 104.9mm 2999cc 16.3:1 Isuzu-patent special aluminium alloy Chain-driven dual overhead camshafts, roller rockers, 4 valves/cylinder Electronic high pressure common rail direct fuel injection with VSS (Variable Swirl System) and intercooled electric control VGS (Variable Geometry System) turbocharger Cast iron upper with induction-hardened cylinder bores, cast alloy lower Euro 5

Manual 3.0L Engine: Isuzu MVL-6S 6-speed manual with high torque capacity and output reduction, 275mm diameter clutch plate and dual mass flywheel 1.9L Engine: Isuzu MVL-6Y 6-speed manual with high torque capacity and output reduction, 275mm diameter clutch plate and single mass flywheel Automatic Aisin AWR6B45 II 6-speed with sequential shift and brake shift lock electronically controlled, tri-mode with fuel-saving lock-up torque converter on gears 3, 4, 5 and 6 ▶ Uphill/Downhill Transmission Control: holds gear in varied-gradient ascents, selects gear on steep descents to hold speed with engine braking 6-speed Manual Automatic 6-speed Manual Automatic 6-speed Manual Automatic 19LTurbo 6-speed Manual Automatic 6-speed Manual Automatic 1 1527 1488 1 2 1 2 2 3 600 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Transmissions	5					
with fuel-saving lock-up torque converter on gears 3, 4, 5 and 6 ▶ Uphill/Downhill Transmission Control: holds gear in varied-gradient ascents, selects gear on steep descents to hold speed with engine braking Ratios: 1 3.0L Turbo 6-speed Manual Automatic Automatic 1.9L Turbo 6-speed Manual Automatic Automatic 1st 4.942 3.600 1st 4.942 3.600 2nd 2.452 2.090 2nd 2.686 2.090 3rd 1.428 1.488 3rd 1.527 1.488 4th 1.000 1.000 4th 1.000 1.000 5th 0.749 0.687 5th 0.749 0.687 6th 0.634 0.580 6th 0.634 0.580 Reverse 4.597 3.732 Reverse 4.597 3.732 Final drive 4x2 3.727 3.727 4x2 4.100 4.100 Snorkelled diff breathers to increase fording depth and reduce mud blockage 2.482 2.482 4x4 low-range 2.482 2.482 2.482	Manual	275mm diameter 1.9L Engine: Isuzu	clutch plate and J MVL-6Y 6-spee	dual mass flywhed manual with high	el n torque capacity a	·	,
Ratios: 1 3.0L Turbo	Automatic					ectronically control	led, tri-mode
Manual Automatic Manual Automatic					varied-gradient asc	ents, selects gear	on steep
4x4 3.727 3.727 - 4.100 Snorkelled diff breathers to increase fording depth and reduce mud blockage Transfer gearing 4x4 low-range 2.482 2.482 2.482 2.482 4x4 high-range 1.000 1.000 1.000 4x4 system "Terrain Command" control with 'shift on the fly' 2-high ←→4-high selection at up to 100km/h, 4-low with rear differential lock	Ratios: 1	1st 2nd 3rd 4th 5th 6th	Manual 4.942 2.452 1.428 1.000 0.749 0.634	Automatic 3.600 2.090 1.488 1.000 0.687 0.580	1st 2nd 3rd 4th 5th 6th	Manual 4.942 2.686 1.527 1.000 0.749 0.634	Automatic 3.600 2.090 1.488 1.000 0.687 0.580
Transfer gearing 4x4 low-range 2.482 2.482 4x4 high-range 1.000 1.000 2x4 system "Terrain Command" control with 'shift on the fly' 2-high ←→4-high selection at up to 100km/h, 4-low with rear differential lock	Final drive	4x4	3.727	3.727		-	
4x4 high-range 1.000 1.000 1.000 4x4 system "Terrain Command" control with 'shift on the fly' 2-high ←→4-high selection at up to 100km/h, 4-low with rear differential lock		Snorkelled diff bre	eathers to increa	se fording depth ar	nd reduce mud blo	ckage	
rear differential lock	Transfer gearing						
Drivetrain system TCS (Traction Control System) on all model variants	4x4 system			'shift on the fly' 2-l	nigh <→ 4-high sele	ection at up to 100	km/h, 4-low with
	Drivetrain system	TCS (Traction Cor	ntrol System) on	all model variants			

Steering

Electric power steering with speed-sensing steering feel (light at low speed, heavy at high speed); tilt and telescopic adjustable steering wheel

Engine-speed-sensitive variable capacity Electric power system; 3.84 turns lock-to-lock via tiltadjustable steering wheel

Chassis

Separate, full-length heavy-duty chassis with 8 cross members on all models

Front suspension

Independent, high-ride, coil springs, gas shock absorbers, upper and lower wishbones, stabiliser bar

Rear suspension

All Cab Chassis models: Heavy Duty alloy-steel overslung long-span semi-elliptic leaf springs; gas shock absorbers

4x2 and 4x4 models: Alloy-steel overslung long-span semi-elliptic leaf springs; gas shock absorbers

Axles

Independent 4x4: fully floating with outer CV, inner double offset joints and equal length driveshafts. Rating: 1450kg

Rigid semi-floating banjo with hypoid final drive and dual tapered needle roller bearings. Rating: 1910kg

Brakes

Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD), Electronic Stability Control (ESC), Emergency Brake Assist (EBA), Traction Control System (TCS), Rollover Mitigation, Hill Start Assist (HSA), Hill Descent Control (HDC) and Trailer Sway Control (TSC)

320mm dia. ventilated front discs with 2-piston calipers, 295mm rear drums

Power-assisted via 10" servo unit; central pull up park brake

Wheels and Tyres

SX	17" x 7" drilled Silver-Finish Steel; 255 / 65 R17 All-Terrain
LS-M	17" x 7" alloy; 255 / 65 R17 All-Terrain
X-RIDER	17" x 7" alloy; 255 / 65 R17 All-Terrain
LS-U and LS-U+	18" x 7.5" alloy; 265 / 60 R18 Highway-Terrain
X-TERRAIN	18" x 7.5" matte Dark Grey Alloy; 265 / 60 R18 Highway-Terrain
All Models	Full size steel spare wheel

Service Plus

Warranty	For the ultimate peace of mind, every Isuzu D-MAX comes standard with a comprehensive, bumper-to-bumper 6 years/150,000km warranty^.
Roadside Assistance	Enjoy up to 7 years Roadside Assistance ^{<} when you complete your scheduled services at a Participating Isuzu UTE Dealer.
Flat Price Servicing	As an owner you will get access to our Flat Price Servicing ⁵ Program. The FPS Program covers the first 5 Scheduled Services at \$449 per service in line with the Scheduled Service Intervals.

The Flat Price Servicing Program ("FPS Program") applies to FPS Eligible Vehicles (excludes Rental & Government Customers) at Participating Isuzu UTE Dealers only. For 24MY and later vehicle models, the Flat Price Servicing covers the first 5 Scheduled Services up to 5 years/75.000km (whichever occurs first). FPS Program is subject to change. For full terms & conditions, current pricing & model eligibility visit isuzuute.com.au/flat-price-service-disclaimer. ^6 vears/150,000km (whichever occurs first), for Isuzu UTE Vehicles with a Warranty Start Date on or after 1/1/19. Excludes travs & accessories. The Roadside Assistance Program ("RSA Program") provides Coverage to RSA Eligible Vehicles (Private, ABN and Business Fleet Customers only) with a Warranty Start Date on or after 1/9/20 for a maximum of 7 years (unlimited kilometres). Initial 13 months Coverage provided from the Warranty Start Date. The Coverage will be reset for another 13 months from each date that a Participating Isuzu UTE Dealer conducts a Scheduled Service on the vehicle. For full terms & conditions visit isuzuute com au/roadside-assistance-disclaimer

Safety

AS	Every D-MAX comes with Isuzu's Intelligent Driver Assistance System (IDAS#) built-in to protect and enhance the driving systems IDAS includes
	the driving experience. IDAS includes smart technologies as well as other
	passive and active safety features.

*IDAS features are designed to assist the driver, but should not be relied upon nor used as a substitute for safe driving practices. Feature operation may vary in different driving conditions. For full explanation of limitations, see Owner's & Driver's Manual

SPECIFICATIONS

SPECIFICATIONS		4x2	2 High-R	lide		4x4												
	Single Cab	Space	Crew	0	0	Single	Space Cab	0	0 0 1	0	Crew	0	0	Crew	0	0	0	
	Chassis (Cab Chassis	Cab Chassis	Crew Cab Ute	Crew Cab Ute	Cab Chassis	Chassis	Cab Ute		Cab Ute	Cab Chassis				Crew Cab Ute		e Cab	
Engine	SX	SX	SX	SX	LS-U	SX	SX	LS-U	SX	SX	LS-M	LS-M	X-RIDER	LS-U	LS-U	LS-U+	X-TEF	
1898cc DOHC 4cyl. with intercooled turbocharger (350Nm, 110kW)	•		•	•						•								
2999cc DOHC 4cyl. with intercooled turbocharger (450Nm, 140kW)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
ransmissions																		
6-speed manual transmission																		
6-speed "Rev-Tronic" automatic transmission with sequential sport mode										•								
safety and Security					•			•	•			•						
					_			_	_	_			_			_		
4-channel 4-sensor Anti-lock Brake System (ABS) with Electronic Brakeforce Distribution (EBD)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Electronic Stability Control (ESC) Traction Control System (TCS)																		
Emergency Brake Assist (EBA)																		
Hill Start Assist (HSA)		•			•		•	•	•	•	•	•	•	•	•	•		
Hill Descent Control (HDC)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Autonomous Emergency Braking (AEB)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Turn Assist with AEB	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Post-Collision Braking	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Forward Collision Warning (FCW)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Misacceleration Mitigation (*AT models only)	•	*	•	•	•	•*	•	•	•*	•	•	•	•	•	•	•		
ntelligent Adaptive Cruise Control (ACC) with Stop and Go functionality Iraffic Sign Recognition (TSR)							•			•	•			•	•	•		
ntelligent Speed Limiter																		
Manual Speed Limiter																		
Lane Departure Warning (LDW)					•		•	•	•	•	•	•	•	•	•	•		
Lane Departure Prevention (LDP)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Lane Keep Assist (LKA)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Emergency Lane Keeping (ELK)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Lane Support System (LSS) Switch (disables LDW, LDP, LKA, ELK)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Driver Attention Assist	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Blind Spot Monitoring (BSM)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Rear Cross Traffic Alert (RCTA) Rear Cross Traffic Braking (RCTB)					•						•	•		•				
BSM/RCTA Auto Switch Off (disables BSM/RCTA when the genuine tow harness is connected)																		
Digital Reversing camera w/ Dynamic Guidelines							•				•			•				
Digital Reversing camera	•	•	•			•	•		•	•	•	•		•	•			
Rear Park Assist Sensors					•			•							•	•		
Front Park Assist Sensors																		
B Airbags: dual front, curtain, side, driver's knee and far side airbags	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Passenger side SRS airbag on/off switch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Height-adjustable upper mounts for front seat belts		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Pre-tensioners with load limiters for front seat belts Pre-tensioners with load limiters for outer rear seat belts	•	•			•	•	•	•	•	•	•	•	•	•	•	•		
3-point retractable seat belts for all rear and centre seating positions																		
ntelligent seatbelt reminder (all seats)	•	•				•	•	•										
2 childseat tethers and ISO FIX compatible anchor points					•		-	-	•	•	•	•	•	•	•	•		
Height-adjustable head restraints for full-size seats		•	•	•	•		•	•	•	•	•	•	•	•	•	•		
ntegrated head restraint on front seats	•					•												
Child-proof rear door locks			•	•	•				•	•	•	•	•	•	•	•		
Single 10 inch servo brake master cylinder	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Side anti-intrusion bars inside all doors		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Engine immobilizer Rear window demister	•				•	•	•	•	•	•	•	•	•	•	•	•		
High Density Polyethylene (HDPE) fuel tank																		
High mount brake light on cabin													•					
Dual horn		•	•		•	•	•	•	•	•	•	•	•	•	•	•		
rotection																		
Under-front steel skid plate					•				•				•					
Steel plate guards: sump, transfer case, fuel tank leading edge; reinforced resin under fuel tank				•	•	•	•		•									
uspension and Brakes					_			_					_					
Standard rear leaf suspension				•	•			•		•		•	•		•	•		
Heavy duty rear leaf suspension	•		•			•					•			•				
Front independent, coil spring suspension w/gas shock absorbers, upper and lower wishbones and stabiliser bar					_	_	_	_	_	_	_	_	_	_	_	_		

SD	EC			NR
3P		CA	V	13

SPECIFICATIONS		4x2	2 High-F	Ride							4	х4					
	Single Cab	Space Cab	Crew Cab	Crew	Crew	Single Cab	Space Cab	Space	Crew Cab	Crew	Crew Cab	Crew	Crew	Crew Cab	Crew	Crew	Crew
	Chassis SX	Chassis SX	Chassis SX	Cab Ute SX	Cab Ute LS-U	Chassis SX	Chassis SX	Cab Ute	Chassis SX	Cab Ute SX	Chassis LS-M	Cab Ute LS-M	Cab Ute X-RIDER	Chassis LS-U	Cab Ute LS-U		e Cab Uto X-TERRA
In-cabin Storage																	
Lower glovebox compartment only	•	•	•	•		•	•		•	•							
Upper and lower glovebox compartments					•			•			•	•	•	•	•	•	•
Power outlet in lower instrument panel	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Centre floor console	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Dual-purpose driver and front passenger cup holder tray	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rear passenger door cup holders			•	•	•			_	•	•	•	•	•	•	•	•	•
Pockets on backs of front seats		_		_	•		_	•			•	•	•	•	•	•	•
Overhead console with twin map lights and flip-down sunglasses case		•	•	•	•	•		•	•	•	•	•	•	•	•	•	•
Front door storage compartment with bottle bulge	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
2 coat hooks			•	•	•			_	•	•	•	•	•	•	•	•	•
Flip up convenience hook behind passenger front seat			_	_	•			•	_		•	•	•	•	•	•	•
Tool storage behind rear seats		_	•	•	•	_	_	_	•	•	•	•	•	•	•	•	•
Tool storage behind front seats	•	•					•	•									
Rear Tub																	
Double-walled ute tub				•	•			•		•		•	•		•	•	•
4 cargo tie-down hooks inside ute tub				•	•			•		•		•	•		•	•	
Under rail tub liner					•			•							•	•	•
2 cargo tie-down hooks inside ute tub																	•
Tailgate Assist				•	•			•		•		•	•		•	•	•
Exterior Style																	
				_	_		_	_		_	_	_		_	_	_	
Short front overhang for optimal manoeuvrability and approach angle	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Halogen multi-reflector projector lens headlights for extra low beam depth & reduced flare & integrated turn indicators	•	•	•	•	_	•	•	_	•	•	_	_	_			_	_
Bi-LED headlights with auto-levelling function and integrated turn indicators			_	_	•		_	•			•	•	•	•	•	•	•
Automatic headlights	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Automatic high beam	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Coming home light	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Headlight Welcome light	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
LED Daytime Running Lights (DRLs)					•			•			•	•	•	•	•	•	•
LED fog lights			_	_	•			•	_		•	•	•	•	•	•	•
Material Black radiator grille	•	•	•	•		•	•		•	•	_	_	•				
Black-Grey radiator grille					_			_			•	•		_		_	
Silky Silver radiator grille					•			•						•	•	•	
Dark Grey radiator grille		_	_	_	_	_	_	_	_	_	_	_	_		_	_	•
Colour-coded front bumper	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Colour-coded integrated rear step bumper				•	•			•		•		•	•		•	•	•
Black integrated rear step bumper		_	_			_	_		_		_		•				
Black rear bumper	•	•	•		_	•	•	_	•		•			•	_	_	
Factory fitted tow bar receiver					•		_	•						•	•	•	•
Space cab rear "wing" doors		•			_		•	•						_	_	_	
Aluminium side steps					•			•					_	•	•	•	
Dark Grey side steps			_	_					_				•				•
Black door and tailgate handles	•	•	•	•		•	•		•	•	_						
Colour-coded door and tailgate handles					_			_			•	•		_		_	
Chrome door and tailgate handles					•			•						•	•	•	
Dark Grey door and tailgate handles													_				•
Basalt Black door and tailgate handles													•				
Lockable tailgate				•	•			•		•		•	•		•	•	•
Dark Grey Aero Sports Bar																	•
Black Sports Bar													•				
Matte Black roller tonneau																	•
Soft tonneau cover																	
Dark Grey front and rear underbody spoilers																	•
Black front underbody spoiler													•				
Dark Grey fender flares																	•
Dark Grey roof rails																	•
Black power door mirrors	•	•	•	•		•	•		•	•							
Colour-coded power door mirrors with integrated turn indicators											•	•					
Basalt Black power door mirrors with integrated turn indicators													•				
Chrome fold-in power door mirrors with integrated turn indicators					•			•						•	•	•	
Dark Grey fold-in power door mirrors with integrated turn indicators																	•
Heated door mirrors					•			•						•	•	•	•
Centre front roof-mounted bee-sting aerial	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
LED rear combination lamps					•			•							•	•	•

SPECIFICATIONS		4x2	2 High-F	Ride							4	х4					
SPECIFICALIUNS																	
	Single Cab Chassis SX	Space Cab Chassis SX	Crew Cab Chassis SX	Crew Cab Ute SX	Crew Cab Ute LS-U	Single Cab Chassis SX	Space Cab Chassis SX	Space Cab Ute LS-U	Crew Cab Chassis SX	Crew Cab Ute SX	Crew Cab Chassis LS-M	Crew Cab Ute LS-M	Crew Cab Ute X-RIDER	Crew Cab Chassis LS-U	Crew Cab Ute LS-U		Crew Cab Ute X-TERRAI
Seating	3/	3/	3/	3/	L3-U	3/	3/	L3-U	3/	3/	L3-IVI	L3-IVI	A-NIDEN	L3-U	L3-U	L3-U+	A-TENNAI
Standard Black cloth seats	•	•	•	•		•	•		•	•							
High Grade cloth seats					•			•			•	•	•	•	•		
Leather Accented seats																•	
Leather Accented seats with Red Stitching		_	_	_	_	_	_	_	_		_	_			_		•
Front bucket whiplash protection seats	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
6-way adjustable driver seat	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	_	
8-way electric adjustable driver seat														_		•	•
Electric adjustable lumbar support (driver seat only) Heated front seats					•			•						•	•	•	•
Split-fold rear seat																	•
Split-fold rear seat with centre arm rest			•	•					•	•							
Rear centre seat headrest																	
			•	•	•				•				•				
Cabin Amenities																	
Dual zone climate control air-conditioning with integrated heater/demister					•			•						•	•	•	•
Manual air-conditioning with integrated heater/demister	•	•	•	•		•	•		•	•	•	•	•				
Rear seat air-conditioning vents			•	•	•	_			•	•	•	•	•	•	•	•	•
Pollen and fine particle air filter	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Power windows with one-touch up/down driver's window with safety stop and delay closing	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Comfort turn signal	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Central locking with keyless entry	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Smart keyless entry					•			•						•	•	•	•
Walk away lock					•		_	•			_			•	•	•	•
Remote key auto re-lock	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Push button start					•			•						•	•	•	•
Remote engine start Power-adjustable door mirrors with turn indicator lights								_			_						•
Power-adjustable door mirrors Power-adjustable door mirrors					•						•		•		•		•
4 speaker sound system																	
6 speaker sound system	_	•	•	•		•	•		•	_							
"Sky Sound" roof-mounted sound system with 8 speakers (mounted in front dash, front doors, rear doors and roo	f)				•									•	•	•	•
9 inch touchscreen display with wireless Apple CarPlay® and wireless Android Auto® with MID Integration					•			•									
8 inch touchscreen display with wireless Apple CarPlay® and wireless Android Auto™	•	•	•	•		•	•		•	•	•	•	•				
Built-in satellite navigation with MID turn-by-turn directions					•			•						•	•	•	•
Rear centre console USB charging port			•	•	•				•	•	•	•	•	•	•	•	•
USB type C port in central instrument panel					•			•						•	•	•	•
USB type C port in Touchscreen	•	•	•	•		•	•		•	•	•	•	•				
USB type C port in rear floor console			•	•	•				•	•	•	•	•	•	•	•	•
USB type A port in Stereo Camera Housing	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Tilt and telescopic adjustable steering wheel with electric power steering	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Urethane steering wheel with cruise, audio and voice recognition controls	•	•	•	•		•	•		•	•	•	•	•				
Leather steering wheel with cruise, audio and voice recognition controls					•			•						•	•	•	•
4.2 inch Smart MID with digital speedometer, safety information, fuel economy and range, odometer, trip	•	•	•	•		•	•		•	•	•	•	•				
information and service reminder	_		•	•		•			•			•	•				
7 inch Smart MID with digital speedometer, safety information, fuel economy and range, odometer, trip information and service reminder					•			•						•	•	•	•
Tyre Pressure Monitoring System (TPMS)																	
Electro-luminescent gauges									•								
"Terrain Command" 4x4 select dial	•		•		•												
Rear differential lock button																	
Rough Terrain Mode button																	
Automatic windshield wipers	•	•	•	•	•												
Intuitive flat wiper blade		•	•	•		_	_	•	_	_	_	_	•	•	•	•	•
Day/night interior rear view mirror	•	•	•	•		•	•		•	•	•	•	•	•	•	•	•
Auto-dimming rear view mirror					•		-	•			_		-	•	•	•	•
Sun visors with vanity mirrors (driver and passenger) and ticket retaining strap (driver)					•			•						•	•	_	-
Sun visors with illuminated vanity mirrors (driver and passenger) and ticket retaining strap (driver)								-							-	•	•
Fixed A-pillar assist-grips for driver and front passenger	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Fixed B-pillar assist-grips for rear passengers			•	•	•		-		•	•	•	•	•	•	•	•	•
Folding assist-grips for driver and front passenger			•	•	•				•	•	•	•	•	•	•	•	•
			•		•						•	•	•	•	•	•	•
Folding assist-grips for rear passengers																	
Carpet flooring				•	•			•		•	-		-	•	•	•	•

Apple CarPlay is a trademark of Apple Inc. Android Auto is a trademark of Google LLC. Not all devices will be compatible & functionality will vary depending on the device. Mobile Data & SMS rates may apply & are the responsibility of the user. Please check your local road rules before using these functions.

FUEL, WEIGHTS			4				4x4														
& DIMENSIONS	Cha Cha	ngle ab assis	Space Cab Chassis SX	C Cha	Crew Cab Chassis SX		rew o Ute	Crew Cab Ute LS-U	Single Cab Chassis SX	Space Cab Space Chassis Cab Ute SX LS-U		Crew Cab Chassis SX	Crew Cab Ute SX		Crew Cab Chassis LS-M	Crew Cab Ute LS-M	Crew Cab Ute X-RIDER	Crew Cab Chassis LS-U	Crew Cab Ute LS-U	Crew Cab Ute	Crew Cab Ute X-TERRAIN
D-MAX ADR 81/02 ^a Fuel Consumption Values	1.9L	3.0L		1.9L	3.0L	1.9L 3.0L							1.9L	3.0L							
Transmission (MT = Manual, AT = Automatic)	MT/AT	MT/AT	AT	AT	AT	AT	AT	AT	MT / AT	AT	AT	MT / AT	AT	AT	AT	AT	AT	AT	AT	AT	AT
FUEL CONSUMPTION (litres/100km)																					
Combined	7.0	8.0	8.0	7.0	8.0	6.7	7.7	8.0	8.0	8.0	8.0	8.0	6.9	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
Urban	7.9	10.2/9.8	9.8	7.9	9.8	8.3	9.5	9.8	10.2/9.8	9.8	9.8	10.2/9.8	8.1	9.8	9.8	9.8	9.8	9.8	9.8	9.8	9.8
Extra Urban	6.6	6.7/6.9	6.9	6.6	6.9	6.0	6.7	6.9	6.7/6.9	6.9	6.9	6.7/6.9	6.3	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9
CO ² (g/km)	104	200/207	207	104	207	177	200	207	206/207	207	207	206/207	100	207	207	207	207	207	207	207	207
Combined	184	206/207	207	184	207 254	177		207 254	, .	254	207	, .	180	207 254	207 254	207	207 254	207 254	207 254	207 254	207 254
Urban Extra Urban	208 174	262/254 174/180	254 180	208 174	180	218 158	246 174	180	262/254 174/180	180	254 180	262/254 174/180	212 165	180	180	254 180	180	180	180	180	180
	174	174/100	100	174	100	100	174	100	174/100	100	100	174/100	100	100	100	100	100	100	100	100	100
Dimensions (mm unless stated otherwise) Wheelbase	21	25	3125	21	125	2.	125	2125	2125	2125	2125	3125	31	25	2125	2125	2125	2125	3125	2125	3125
Overall length		25 40	5300		300		280	3125 5285	3125 5340	3125 5300	3125 5285	5300	52		3125 5300	3125 5280	3125 5280	3125 5300	5285	3125 5285	5310
Overall width (excluding door mirrors)		370	1870		370		370	1870	1870	1870	1870	1870	18		1870	1870	1870	1870	1870	1870	1880
Overall height (*depends on body fitted)		90*	1800*	18			785	1790	1790*	1800*	1790	1800*	17		1800*	1785	1785	1805*	1790	1790	1810
Front overhang		90	890		90		90	890	890	890	890	890	89		890	890	890	890	890	890	905
Rear overhang (*depends on body fitted)	13		1270*	12			250	1250	1310*	1270*	1250	1270*	12		1270*	1250	1250	1270*	1255	1255	1255
Wheel track width		70	1570		570		570	1570	1570	1570	1570	1570	15		1570	1570	1570	1570	1570	1570	1570
Ground clearance		35	235		35		35	240	235	235	240	235	23		235	235	235	240	240	240	240
Turning circle diameter between kerbs (metres)		2.5	12.5		2.5		2.5	12.5	12.5	12.5	12.5	12.5	12.5		12.5	12.5	12.5	12.5	12.5	12.5	12.5
Approach angle	29	.6°	29.6°	29	9.6°	29.6	6°/30°	30.5°	29.6°	29.6°	30.5°	29.6°	30)°	29.6°	30°	26.9°	30°	30.5°	30.5°	27.3°
Departure angle	24	.6°	25.3°	25	5.3°	23	3.9°	19.0°	24.6°	25.3°	19.0°	25.3°	23	.9°	25.3°	23.9°	23.9°	20.6°	19.0°	19.0°	19.0°
Ramp-over angle	23	.9°	23.9°	23	3.9°	23	3.3°	23.8°	23.9°	23.9°	23.3°	23.9°	23	.3°	23.9°	23.3°	23.3°	24.3°	23.8°	23.8°	23.8°
Load area (mm)																					
Cab to rear axle	12	40	765	4	50	4	50	450	1240	765	765	450	45	50	450	450	450	450	450	450	450
Length (top)		-	-		-	14	195	1495	-	-	1805	-	14	95	-	1495	1495	-	1495	1495	1495
Length (floor) (*inside genuine accessory tray body)	25	50*	2100*	18	00*	15	570	1570	2550*	2100*	1835	1800*	15	70	1800*	1570	1570	1800*	1570	1570	1570
Maximum width (*inside genuine accessory alloy tray body)	17	77*	1777*	17	77*	15	530	1530	1777*	1777*	1530	1777*	15	30	1777*	1530	1530	1777*	1530	1530	1530
Width between wheel houses		-	-		-	11	122	1122	-	-	1122	-	11:	22	-	1122	1122	-	1122	1122	1122
Depth		-	-		-	4	90	490	-	-	490	-	49	90	-	490	490	-	490	490	490
Interior (mm)																					
Leg room - front	10	75	1075	10)75	10)75	1075	1075	1075	1075	1075	10	75	1075	1075	1075	1075	1075	1075	1075
Leg room - rear		-	-	9	05	9	05	905	-	-	-	905	90)5	905	905	905	905	905	905	905
Shoulder room - front	14	60	1460	14	160	14	160	1460	1460	1460	1460	1460	14	60	1460	1460	1460	1460	1460	1460	1460
Head room - front	10	20	1020	10)20	10	020	1020	1020	1020	1020	1020	10	20	1020	1020	1020	1020	1020	1020	1020
Rear cargo space		-	730		-		-	-	-	730	730	-			-	-	-	-	-	-	-
Mass (kg)																					
Gross Vehicle Mass (GVM)	3000	3000	3000	3000	3000	3000	3000	3000	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100
Kerb weight [^]	1600/1620	1695/1705	1780	1745	1830	1870	1950	2015	1785/1790	1865	2065	1910/1915	1955	2035	1910	2030	2055	1965	2105	2110	2170
Payload (cab chassis models: final mass depends on body fitted)	1400/1380	1305/1295	1220	1255	1170	1130	1050	985	1315/1310	1235	1035	1190/1185	1145	1065	1190	1070	1045	1135	995	990	930
Gross Combination Mass (GCM)	5300/5500	5850	5850	5500	5850	5500	5850	5850	6000	6000	6000	6000	5500	6000	6000	6000	6000	6000	6000	6000	6000
Maximum towing mass (braked trailer)	2800/3000	3500	3500	3000	3500	3000	3500	3500	3500	3500	3500	3500	3000	3500	3500	3500	3500	3500	3500	3500	3500
Maximum towing mass (non-braked trailer)	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750	750
Maximum tow ball download (when fitted with genuine Isuzu UTE tow kit)	280/300	350	350	300	350	300	350	350	350	350	350	350	300	350	350	350	350	350	350	350	350
Fuel tank capacity (litres)	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76	76

^AFuel consumption & emissions figures based on ADR 81/02 & are to be used for vehicle comparison purposes only. Actual fuel consumption & emissions will vary depending on many factors including, but not limited to, traffic conditions, individual driving style & vehicle condition. ^Kerb weight - unladen mass of vehicle & full tank of fuel, excludes tray body for cab chassis vehicles. Fuel weight ratio is based on Fuel Standard (Automotive Diesel) Determination 2001.

-Payload equals GVM minus kerb weight.

CAB CHASSIS BODY STYLES AND DIMENSIONS (24MY)



SX Single Cab Chassis 4x2 & 4x4



SX Space Cab Chassis 4x2 & 4x4




SX Crew Cab Chassis 4x2 & 4x4



LS-M Crew Cab Chassis 4x4










































CAB CHASSIS AND UTE BODY STYLES AND DIMENSIONS (24MY)



LS-U Crew Cab Chassis 4x4




SX Crew Cab Ute 4x2 & 4x4



LS-M Crew Cab Ute 4x4




X-RIDER Crew Cab Ute 4x4












































UTE BODY STYLES AND DIMENSIONS (24MY)




LS-U Space Cab Ute 4x4














LS-U Crew Cab Ute 4x2 & 4x4 LS-U+ Crew Cab Ute 4x4














X-TERRAIN Crew Cab Ute 4x4









COLOURS AND TRIM (24MY)

Body Colours



Basalt Black mica



Mercury Silver metallic



Mineral White



Neptune Blue mica



Obsidian Grey mica



Magnetic Red mica (X-RIDER, LS-U Range & X-TERRAIN Exclusive)



Granite Grey mica (X-RIDER, LS-U Range & X-TERRAIN Exclusive)



Moonstone White pearl
(LS-U Range & X-TERRAIN Exclusive)



Sunstone Orange mica (X-TERRAIN Exclusive)

Interior Trim



Standard Black Cloth (On SX models)

High Grade Cloth
(On LS-M, X-RIDER, LS-U models)

Leather Accented[†] (On LS-U+)

Leather Accented' with Red Stitching (On X-TERRAIN)

TRAY STYLES

Economy Alloy



General Purpose Alloy



Heavy Duty Alloy



Heavy Duty Steel



Mine Specification Steel



Single





































